

T115

Utility, Series 6
113 PS



A powerful utility tractor designed to conquer the most demanding tasks

Engineered with advanced technology, the T115 delivers powerful performance that is immediately felt in the field, providing greater ease in operation and confidently handling even the toughest jobs.



1. Centralized control panel



3. External control switch



5. 8-port rear remote hydraulic valve



2. Air suspension seat



4. Digital panel



6. Rearview camera



High-powered Deutz engine

Built with precision German engineering, Deutz engines offer high power and torque, even at low RPMs. Their longer lifespans and high reliability make them an ideal choice to boost productivity.



Comfort suspension seat

Comfort suspension seats provide excellent ride quality and minimize fatigue during long hours of operation.



6-port external rear remotes and hydraulic top link

2 separate remotes for the top link means that all 6 external rear remotes can be used to mount a variety of attachments. External top link buttons make attaching and detaching attachments easy.



Smart break

By controlling power with the brake alone—without operating the clutch while driving—stopping and starting becomes much easier and more convenient.



Leveling control

Equipped with a proportional control valve and gyro sensor, it detects and corrects vehicle tilt more quickly and precisely. This enables stable operation even on slopes, helping crops grow more evenly and improving productivity.



Hand Clutch / Power Shift

With the main shift lever, you can change gears easily at the touch of a button without pressing the clutch pedal. Fine gear adjustments are also possible using the two (+, -) buttons.

Technical specifications

ENGINE

Engine Manufacturer	Deutz TCD 3.6 L4
Type	Turbocharger
Gross engine power	113 PS 83 kW
PTO power	109 PS 80 kW
Rated engine speed	2200 rpm
No. of cylinders	4
Displacement	3621 cc 221 cu. in.
Air cleaner	Dual dry
Alternator	12V, 120A
Fuel system	CRDI

POWERTRAIN

Transmission type	Power shuttle
No. of speeds	F32 × R32
Max. traveling speed	37 km/h 23 mph
Brakes	Wet, Multi disc
Steering	Hydrostatic
Clutch	Wet/Multi disc

CAPACITIES

Fuel tank	120 L 31.7 gal
Coolant	18 L 19.0 qt
Crankcase	8 L 8.5 qt
Transmission/Hydraulics system	75 L 19.8 gal
Front axle	17.5 L 4.6 gal

PTO

PTO type	Independent
PTO control	Electric/Hydro
PTO rear	540/750/1000 rpm

HYDRAULIC SYSTEM

Pump type	Gear pump
Implement flow	54.1 L/min 14.3 gpm
Steering flow	26.8 L/min 7.1 gpm
Total flow	81.1 L/min 21.4 gpm
Category, 3-point hitch	Cat 2
Hitch lift capacity	3309 kg 7294.9 lb
Hitch lift capacity at 24 inches behind link ends	2722 kg 6006.8 lb
Lift control type	Position/Draft/TBS
No. of standard remote valves	6

DIMENSIONS & WEIGHTS

Overall length with 3-point hitch	4450 mm 175.2 in.
Overall width	2270 mm 89.4 in.
Wheelbase	2380 mm 93.7 in.
Height to top of Cabin	2850 mm 112.2 in.
Min. ground clearance	425 mm 16.7 in.
Min. turn radius with brakes	(L) 3400 mm 133.86 in. / (R) 3410 mm 134.25 in.
Min. turn radius without brakes	(L) 4050 mm 159.45 in. / (R) 4090 mm 161.02 in.
Weight with cab	4055 kg 8940 lb
Weight with ROPS	-
Track width	F: 1720 mm / R: 1650 mm

STANDARD TIRES

Agricultural - Front	13.6-24
Agricultural - Rear	18.4-34

Upgrades for the Series 6 T115

Complement the capabilities of your TYM tractor with compatible accessories and options.

ACCESSORIES

Front counterweights





Designed for your world

TYM creates tractors that bring together alluring form, advanced function and accessible value. Through Korean expertise in design, engineering and manufacturing, the company helps owners overcome every obstacle as they shape the world around them.

Headquartered in Korea with distribution across North America, Europe, and Asia, and assembly operations in the USA, TYM has been empowering customers for over 70 years.

www.tym.world