

T4058PC

Compact, Series 4
58 hp



A premium compact tractor that delivers power and efficiency

When it comes to all-around productivity, look no further than the T4058PC. This compact tractor is designed to boost output, delivering impressive efficiency and deluxe features that have become the hallmark of the TYM Series 4.



1. New iconic hood



3. Electronic 4WD engagement



2. Tilt steering wheel



4. Digital instrument panel



5. Comfortable suspension seat



6. External hitch switch



Eco-friendly TYM Tier 4 engine

Equipped with the Turbo charged company designed-and-made TYM engine, the tractor is designed to be eco-friendly and fuel efficient but makes no compromise on performance and reliability.



MYTYM telematics system

Through MYTYM's remote diagnostics service, check the real-time monitoring, enhanced maintenance and improved operational efficiency.



Power shuttle and D-clutch

Power shuttle enhances efficiency for tasks requiring frequent directional changes in tighter spaces without stepping on the clutch pedal and enhance the maneuverability.



Electronic hydraulic control system

The system allows for easy control of operations for 3pt-hitch control, turn/back up and draft sensitivity adjustment and giving operators full control over their task at hand.



Front LED work lighting bar

The cabin version introduces an LED bar-type front worklight, ideal for low-light tasks and extended operational hours and enhance the productivity.



6-Ports front/rear external hydraulic valve with 2-buttons joystick

The 6-port front selective control valves allows for a wide variety of implements to be installed. This allows for easy and efficient grapple operation.

Technical specifications

ENGINE	
Engine manufacturer	TYM T2300T1-UTC_4
Type	Turbo charger
Gross engine power	58 hp 43.3 kW
PTO power	48 hp 35 kW
Rated engine speed	2600 rpm
No. of cylinders	4
Displacement	139.5 cu. in. 2287 cc
Air cleaner	Dry element
Alternator	12V, 70A
Fuel system	IDI
POWERTRAIN	
Transmission type	Power shuttle
No. of speeds	F12 x R12
Max. traveling speed	24.04 mph 38.7 km/h
Brakes	Wet, Multi disc
Steering	Hydrostatic
Clutch	Wet Multi disc
CAPACITIES	
Fuel tank	15.3 gal 58 L
Coolant	6.2 qt 5.9 L
Crankcase	4.8 qt 4.5 L
Transmission/Hydraulics system	11.62 gal 44 L
Front axle	6.8 qt 6.4 L

PTO	
PTO type	Independent
PTO control	Wet, Multi-disc
PTO rear	540 rpm
HYDRAULIC SYSTEM	
Pump type	Single gear pump
Implement flow	11.4 gpm 43.2 L/min
Steering flow	5.13 gpm 19.44 L/min
Total flow	16.5 gpm 62.6 L/min
Category, 3-point hitch	II
Hitch lift capacity	4409 lb 2000 kg
Hitch lift capacity at 24 inches behind link ends	3748 lb 1700 kg
Lift control type	Position
No. of standard remote valves	Loader: 6 / Rear: 6
DIMENSIONS & WEIGHTS	
Overall length with 3-point hitch	141.5 in. 3595 mm
Overall width	68.9 in. 1750 mm
Wheelbase	78.7 in. 2000 mm
Height to top of ROPS	-
Height to top of cabin	99.2 in. 2520 mm
Min. ground clearance	18.1 in. 460 mm
Min. turn radius with brakes	(L) 121.9 in. 3098 mm / (R) 125.3 in. 3184 mm
Min. turn radius without brakes	(L) 139.7 in. 3550 mm / (R) 141.9 in. 3606 mm
Weight with ROPS	-
Weight with cab	4951.5 lb 2246 kg
STANDARD TIRES	
R1 Agricultural - Front	9.5-20
R1 Agricultural - Rear	14.9-28
R4 Industrial - Front	10.5/80-18
R4 Industrial - Rear	16.9-24
Golf Tires - Front	29x12.5-15
Golf Tires - Rear	44x18.00-20

Upgrades for the Series 4, T4058PC

Complement the capabilities of your TYM tractor with compatible accessories and options.

Accessories



Options

Tire	R1 Agricultural Tires	F 9.5 - 20	R 14.9-28
Tire	R4 Industrial Tires	F 10.5/80 - 18	R 16.9-24



Designed for your world

TYM creates tractors that bring together alluring form, advanced function and accessible value. Through Korean expertise in design, engineering and manufacturing, the company helps owners overcome every obstacle as they shape the world around them.

Headquartered in Korea with distribution across North America, Europe, and Asia, and assembly operations in the USA, TYM has been empowering customers for over 70 years.

www.tym.world