

T264

Sub-Compact, Series 2
24 hp



A versatile sub-compact tractor designed for maneuverability

Get more work done in less time with the T264. This sub-compact tractor balances impressive lift capabilities and high maneuverability to stand out as an all-around multi-tasking machine.



1. Optional loader with high lift capacity



3. Dual filter air cleaner



2. PTO on/off switch



4. Cruise control



5. Foldable ROPS



6. Joystick control for front loader



Ergonomic features for enhanced productivity

A wide operator cabin with a flat floor offers good visibility and ample leg room, promoting comfortable operation. All controls are within arm's reach, including a dial to control the cutting height of the mid-mount implement. The accelerator, brake pedal, differential lock, and parking brake are easily accessible on the floor of the cabin, located precisely where you expect them to be. These features make this tractor easy to operate, even for novice drivers.



Dual filter air cleaner for engine longevity

An additional filter protects the tractor's engine from harmful particles, drastically extending the engine life.



Simple and effective TYM engine

This tractor comes equipped with the South Korean-made TYM engine and is naturally aspirated. The minimal design and minimized emissions results in a more efficient engine, lowering fuel and maintenance costs.



Cast iron components for sturdier connections

For enhanced durability under heavier loads, the rear of this tractor features robust cast-iron components to connect attachments. The material improves hydraulic efficiency and extends component lifecycles.



High-capacity fuel tank for time-intensive work

The high capacity fuel tank allows drivers to take on jobs for longer periods without stopping for fuel. This is in addition to the engine, which promotes fuel-efficient operation and increases the time before a refuel.



Easy to open hood for convenient maintenance

The tractor hood can be opened in one motion, providing easy access to the engine and other systems for daily checks, routine service, and maintenance. The side panel can also be removed easily without the need for specialized tools.



3-point hitch with powerful lift capacity

The 3-point linkage on the rear has an impressive lift capacity that reaches the end ball joint. The rear PTO control can be used to adjust rpm based on the task, increasing it for more intensive applications like slashing and digging.



HST for infinitely variable drive speed

Responsive hydrostatic controls offers a smooth ride for operators, from the forward and reverse pedal to the powered steering wheel. These controls reduce the need for operator effort during a range of tasks, particularly while operating the optional front-end loader.

Technical specifications

| ENGINE | |
|--------------------------------|------------------------|
| Engine manufacturer | TYM T1100N2 |
| Type | Natural aspiration |
| Gross engine power | 24 hp 18 kW |
| PTO power | 18.3 hp 13.6 kW |
| Rated engine speed | 2800 rpm |
| No. of cylinders | 3 |
| Displacement | 71.7 cu. in. 1175 cc |
| Air cleaner | Single dry |
| Alternator | 12V, 50A |
| Fuel system | IDI |
| POWERTRAIN | |
| Transmission type | HST |
| No. of speeds | Infinite 2-Range |
| Max. traveling speed | 12.9 mph 20.8 km/h |
| Brakes | Wet disc |
| Steering | Hydrostatic |
| Clutch | Dry single plate |
| CAPACITIES | |
| Fuel tank | 6.6 gal 25 L |
| Coolant | 5.9 qt 5.5 L |
| Crankcase | 4.5 qt 4.3 L |
| Transmission/Hydraulics system | 4.7 gal 17.8 L |
| Front axle | 4.7 qt 4.4 L |

| PTO | |
|---|--|
| PTO type | Independent |
| PTO control | Electric/Hydro |
| PTO rear | 540 rpm |
| HYDRAULIC SYSTEM | |
| Pump type | Dual gear pump |
| Implement flow | 4.4 gpm 16.6 L/min |
| Steering flow | 2.7 gpm 10.4 L/min |
| Total flow | 7.1 gpm 26.9 L/min |
| Category, 3-point hitch | I |
| Hitch lift capacity | 1534 lb 696 kg |
| Hitch lift capacity at 24 inches behind link ends | 1102 lb 500 kg |
| Lift control type | Position |
| No. of standard remote valves | Optional (1) |
| DIMENSIONS & WEIGHTS | |
| Overall length with 3-point hitch | 107.8 in. 2740 mm |
| Overall width | 52.8 in. 1342 mm |
| Wheelbase | 58.3 in. 1480 mm |
| Height to top of ROPS | 89.8 in. 2280 mm |
| Height to top of cabin | - |
| Min. ground clearance | 7.7 in. 196 mm |
| Min. turn radius with brakes | 98.5 in. 2502 mm |
| Min. turn radius without brakes | 105.5 in. 2682 mm |
| Weight with ROPS | 1881 lb 853 kg |
| Weight with cab | - |
| STANDARD TIRES | |
| R3 Turf - Front | Turf Master 23x8.50-12 NHS TL 4PR |
| R3 Turf - Rear | Multi-Trac CS 33x12.50-16.5 NHS TL 4PR |
| R4 Industrial - Front | Trac Chief 23x8.50-12 NHS TL 4PR |
| R4 Industrial - Rear | Trac Chief 12-16.5 NHS TL 6PR |

TX2000 Front-End Loader

Attachments

Enhance the functionality of your TYM sub-compact tractor with the TX2000 front-end loader. With impressive lift capacity and height, this TYM front-end loader can help you lift, move and handle material more effectively.

| | |
|--|-------------------------|
| Lift height | 86.9 in. 2207 mm |
| Lift capacity at pivot point (max. height) | 1380 lb 626 kgf |
| Bucket capacity | 6.4 cu. ft 0.18 cu. m |

| CAPACITIES & REACH | |
|---|-----------------------------|
| Lift height | 86.9 in. 2207 mm |
| Max. lift height under level bucket | 81.9 in. 2081 mm |
| Clearance with bucket dumped | 64.6 in. 1641 mm |
| Reach at maximum lift height | 21.8 in. 553 mm |
| Max. dump angle | 53° |
| Reach with bucket on ground | 58.5 in. 1487 mm |
| Max. rollback angle | 30° |
| Digging depth | 3.2 in. 82 mm |
| Lift capacity at pivot point (max. height) | 1380 lb 626 kgf |
| Breakout force at ground level, pivot pins | 2059 lb 934 kgf |
| Bucket rollback force at ground line | 1596 lb 724 kgf |
| Bucket capacity | 6.4 cu. ft 0.18 cu. m |
| Self leveling | NA |
| Relief valve setting (loader control valve) | 2276 psi 160 kg/sq. cm |
| Compatible bucket sizes | 66" Front-end loader bucket |



| DIMENSIONS & WEIGHTS | |
|--|-----------------------------|
| Overall height in carry position | 46.1 in. 1170 mm |
| Depth of Attachment (to the back of the inner shell) | 16.7 in. 423 mm |
| Height of Attachment | 19 in. 484 mm |
| Length of Attachment (to pivot pin) | 23.3 in. 592 mm |
| Weight of boom & quick attach mechanism (1) | 363.8 lb 165 kg |
| Weight of mounting frame (2) | 116.8 lb 53 kg |
| Weight of bucket (3) | 202.8 lb 92 kg |
| Loader total weight (1+2+3) | 683.4 lb 310 kg |
| Lift cylinder | 1.8 × 1.2 in. 45 × 30 mm |
| Bucket cylinder | 1.97 × 1.2 in. 50 × 30 mm |
| Attachment used for specification | 59.8 in. 1520 mm |
| CYCLE TIMES | |
| Boom raising time | 4.1 sec |
| Boom lowering time | 2.3 sec |
| Bucket rollback time | 2.6 sec |
| Bucket dumping time | 4.1 sec |
| COMPATIBLE BUCKET SIZES | |
| TYM's multi-purpose buckets are capable of bulldozing, scraping, loading, metering, moving, and clamping material. | |
| 60" Front-End Loader bucket | |

MM60R-1 Mid-Mount Mower

Attachments

Built with 60-inch working width cutting deck and 5.12-inch transport height, the TYM MM60R-1 mid-mount mower is designed to optimize your cutting time and improve cut quality.

| | |
|----------------|---------------------|
| Blade velocity | 18362 fpm |
| Blade length | 20.8 in. 528.3 mm |
| Working width | 1.5 in. 38.2 mm |

| PERFORMANCE | |
|-----------------------------|-------------------------|
| No. of blades | 3 EA |
| Blade velocity | 18362 fpm |
| Blade length | 20.8 in. 528.3 mm |
| Power rating | 20-25 hp 14.9-18.6 kW |
| GENERAL | |
| Type | Side discharge |
| Mounting method | Parallel linkage |
| Lift linkage type | Lower link lift |
| Adjustment of increment | Dial gauge |
| Dial gauge hole | 7 EA |
| Dial gauge gab between hole | 0.5 in. 12.7 mm |
| Dial gauge total gab | 3 in. 76.2 mm |
| Universal joint | Ø21.6 × 525 L |
| Wheel | 4 EA |
| Assistant wheel | 1 EA |
| Belt | V-Belt |
| Color | Super RED |
| Deck thickness | 272 lb 123.4 kg |



| DIMENSIONS & WEIGHTS | |
|----------------------|-----------------------------|
| Working width | 1.5 in. 38.2 mm |
| Length | 2.92 in. 74.3 mm |
| Width | 0.28 in. 7.2 mm |
| Height | 0.13 in. 3.3 mm |
| Weight | 60 in. 1524 mm |
| Cutting height | 1 - 4 in. 25.4 - 101.6 mm |
| Transport height | 5.12 in. 130 mm |

TB65 Backhoe

Attachments

The TB65 is engineered to handle your scaled-up requirements. This TYM backhoe attachment offers enhanced functionality without compromising balance with an enhanced dig depth and wider swing angle.

| | |
|----------------|---------------------|
| Digging depth | 80.4 in. 2042 mm |
| Loading height | 63 in. 1602 mm |
| Backhoe reach | 117.7 in. 2989 mm |

| PERFORMANCE | |
|--------------------------------------|---------------------|
| Digging depth | 80.4 in. 2042 mm |
| Loading height | 63 in. 1602 mm |
| Max. leveling angle | 10° |
| Angle of departure | 15° |
| CAPACITIES & REACH | |
| Backhoe reach | 117.7 in. 2989 mm |
| Swing angle | 180° |
| Bucket rotation | 180° |
| Stabilizer spread (lowered position) | 70.5 in. 1792 mm |
| Stabilizer spread (raised position) | 60 in. 1525 mm |



| DIMENSIONS & WEIGHTS | |
|--|--------------------|
| Transport overhang | 45.7 in. 1162 mm |
| Transport height (max.) | 81.1 in. 2060 mm |
| Compatible bucket sizes | 9" backhoe bucket |
| Compatible bucket sizes | 12" backhoe bucket |
| Compatible bucket sizes | 16" backhoe bucket |
| Compatible bucket sizes | 18" backhoe bucket |
| COMPATIBLE BUCKET SIZES | |
| TYM's multi-purpose buckets are capable of bulldozing, scraping, loading, metering, moving, and clamping material. | |
| Small_09 | Small_12 |
| Small_16 | Small_18 |

Upgrades for the Series 2, T264

Complement the capabilities of your TYM tractor with compatible accessories and options.

Accessories

| |
|-------------------------|
| Block heater |
| Auxiliary hydraulic kit |
| BHPAD100 Street Pads |
| Rear wiper kit |
| Mid-PTO kit |
| Front counterweights |
| Mulching kits |
| TB65A Mechanical Thumb |



Options

| | | | |
|-------|------------------------|--------------------------------------|--|
| Tire | R3 Turf Tires | F Turf Master 23x8.5 - 12 NHS TL 4PR | R Multi-Trac CS 33x12.50-16.5 NHS TL 4PR |
| Tire | R4 Industrial Tires | F Trac Chief 23x8.50 - 14 NHS TL 4PR | R Trac Chief 12-16.5 NHS TL 6PR |
| Tire | R4 Lg Industrial Tires | F Trac Chief 23x8.50 - 14 NHS TL 4PR | R Trac Chief 14-17.5 NHS TL 6PR |
| Cabin | CAB234H | | |



Designed for your world

TYM creates tractors that bring together alluring form, advanced function and accessible value. Through Korean expertise in design, engineering and manufacturing, the company helps owners overcome every obstacle as they shape the world around them.

Headquartered in Korea with distribution across North America, Europe, and Asia, and assembly operations in the USA, TYM has been empowering customers for over 70 years.

www.tym.world