

2500

Sub-Compact, Series 2
24 hp



A versatile sub-compact tractor for projects of all sizes

The 2500 is a highly maneuverable sub-compact tractor that offers both versatility and power, and perfect for everyone from hobbyists to groundskeepers. Experience the convenience of a ride-on mower with the capabilities of a full-size tractor.



1. New iconic hood



3. Ergonomic lever



2. Comfortable suspension seat



4. Responsive forward/reverse HST (2500H)



5. PTO lever



6. 2 port rear hydraulic control (optional)



Eco-friendly 3-cylinder Stage V TYM engine

The 2500 is equipped with a naturally aspirated engine designed and manufactured by TYM. While designed to be fuel efficient and eco-friendly, the TYM engine makes no compromise on performance and reliability.



Four-wheel drive

Standard four-wheel drive on these tractors result in higher work efficiency, even in the most challenging environments.



Cruise control (HST)

The cruise control function allows you to set and maintain engine RPM, regardless of the tractor's load conditions.



High-visibility instrumental panel

Be fully aware of your working conditions. The clear instrumental panel on TYM tractors enables you to keep track of essential information such as speed, fuel, and tractor status at all times.



Foldable ROPS

The Roll Over Protective Structure (ROPS) of the tractor is designed to be folded, allowing for easy storage in garages, sheds, and other low-ceiling structures.



High ground clearance

An impressive ground clearance of 307mm makes it possible for to operate without difficulty on rocky or uneven terrain

Technical specifications

ENGINE		PTO	
Engine manufacturer	TYM T1100N2	PTO type	Live
Type	Natural aspiration	PTO control	Manual
Gross engine power	24 hp 18 kW	PTO rear	Rear: 540/1000 rpm Mid: 2500 rpm
PTO power	20.7 hp 15.5 kW	HYDRAULIC SYSTEM	
Rated engine speed	2800 rpm	Pump type	Gear pump
No. of cylinders	3	Implement flow	17.6 L/min 4.7 gpm
Displacement	1175 cc 71.7 cu. in.	Steering flow	12.6 L/min 3.3 gpm
Air cleaner	Dry element	Total flow	30.2 L/min 7.9 gpm
Alternator	12V, 60A	Category, 3-point hitch	I
Fuel system	Water-cooled diesel	Hitch lift capacity	512 kg 1129 lb
POWERTRAIN		Hitch lift capacity at 24 inches behind link ends	328 kg 724 lb
Transmission type	2500R: Constant mesh 2500H: HST	Lift control type	Position
No. of speeds	2500R: F6 x R2 2500H: 2 Range	No. of standard remote valves	Optional (2)
Max. traveling speed	2500R: 19.2 km/h 11.9 mph 2500H: 21.5 km/h 13.4 mph	DIMENSIONS & WEIGHTS	
Brakes	Wet, Multi disc	Overall length with 3-point hitch	3055 mm 120.3 in.
Steering	Hydrostatic	Overall width	1321mm 52.0 in.
Clutch	Dry single plate	Wheelbase	1502 mm 59.1 in.
CAPACITIES		Height to top of ROPS	F-ROPS : 2058 mm 81.0 in. ROPS : 2253 mm 88.7 in.
Fuel tank	23 L 6.0 gal	Height to top of cabin	2139 mm 84.2 in.
Coolant	5 L 5.3 qt	Min. ground clearance	F-ROPS & ROPS: 375 mm 14.8 in. Cab: 375 mm 14.8 in.
Crankcase	3.2 L 3.4 qt	Min. turn radius with brakes	2240 mm 88.2 in.
Transmission/Hydraulics system	2500R: 14 L 3.7 gal 2500H: 10 L 2.6 gal	Min. turn radius without brakes	2700 mm 106.3 in.
Front axle	3.3 L 3.5 qt	Weight with ROPS	F-ROPS: 924 kg 2037 lb ROPS: 888 kg 1958 lb
		Weight with cab	2500R: 1035 kg 2281.8 lb 2500H: 1019 kg 2246.5 lb

STANDARD TIRES

R1 Agricultural - Front	1: 6-12 4PR 2: 6-12 4PR
R1 Agricultural - Rear	1: 9.5-16 6PR 2: 9.5-18 8PR
R3 Turf - Front	23x8.50-12
R3 Turf - Rear	33x12.50-16.5
R4 Industrial - Front	23x8.50-12
R4 Industrial - Rear	12-16.5

BL00SL Front-End Loader

Attachments

The BL00SL front-end loader takes advantage of the power and durability of compatible TYM sub-compact tractors. Ideal for tasks that require more strength, these front-end loaders can help you get your tasks done more efficiently.



CAPACITIES & REACH

Lift height	2148 mm 84.6 in.
Max. lift height under level bucket	2017 mm 79.4 in.
Clearance with bucket dumped	1656 mm 65.2 in.
Reach at maximum lift height	463 mm 18.2 in.
Max. dump angle	42°
Reach with bucket on ground	1466 mm 57.7 in.
Max. rollback angle	35°
Digging depth	175 mm 6.9 in.
Lift capacity at pivot point (max. height)	596 kgf 1314 lb
Breakout force at ground level, pivot pins	889 kgf 1960 lb
Bucket rollback force at ground line	699 kgf 1541 lb
Bucket capacity	0.13 cu. m 4.6 cu. ft
Relief valve setting (loader control valve)	160 kg/sq. cm 2276 psi
Compatible bucket sizes	66" Front-end loader bucket

DIMENSIONS & WEIGHTS

Overall height in carry position	1176 mm 46.3 in.
Depth of Attachment (to the back of the inner shell)	467 mm 18.4 in.
Height of Attachment	484 mm 19.1 in.
Length of Attachment (to pivot pin)	585.6 mm 23.1 in.
Weight of boom & quick attach mechanism (1)	136 kg 299 lb
Weight of mounting frame (2)	68 kg 150 lb
Weight of bucket (3)	55 kg 121 lb
Loader total weight (1+2+3)	259 kg 570 lb
Lift cylinder	45 × 30 mm 1.8 × 1.2 in.
Bucket cylinder	50 × 30 mm 2.0 × 1.2 in.
Attachment used for specification	1220 mm 48 in.

CYCLE TIMES

Boom raising time	3.8 sec
Boom lowering time	2.1 sec
Bucket rollback time	2.7 sec
Bucket dumping time	4.2 sec

BM60E Mid-Mount Mower

Attachments

Built with 60-inch working width cutting deck and 5.12-inch transport height, the TYM BM60E mid-mount mower attachment is designed to optimize your cutting time and improve cut quality.



PERFORMANCE

No. of blades	3 EA
Blade velocity	3363 fpm
Blade length	528.3 mm 20.8 in.
Power rating	13.4-14.9 kW (18-20 hp)

GENERAL

Type	Side discharge
Mounting method	Parallel linkage
Lift linkage type	Lower link lift
Adjustment of increment	Dial gauge
Dial gauge hole	7 EA
Dial gauge gap between hole	12.7 mm 0.5 in.
Dial gauge total gap	76.2 mm (3 in.)
Universal joint	Ø21.6 × 525 L
Wheel	4 EA
Assistant wheel	1 EA
Belt	V-Belt
Color	RED
Deck thickness	3.3 mm 0.13 in.

DIMENSIONS & WEIGHTS

Working width	1524 mm 60 in.
Length	38.2 mm 1.5 in.
Width	74.3 mm 2.92 in.
Height	7.2 mm 0.28 in.
Weight	123.4 kg 272 lb
Cutting height	25.4 - 101.6 mm 1 - 4 in.
Transport height	129.5 mm 5.1 in.

BH100 Backhoe

Attachments

The TYM BH100 backhoe attachment is engineered to maximize the efficiency and enhance the productivity of your sub-compact tractor.

Digging depth	1920 mm 75.6 in.
Loading height	1592 mm 62.7 in.
Backhoe reach	2740 mm 107.9 in.

PERFORMANCE

Digging depth	1920 mm 75.6 in.
Loading height	1592 mm 62.7 in.
Max. leveling angle	10°
Angle of departure	20°

CAPACITIES & REACH

Backhoe reach	2740 mm 107.9 in.
Swing angle	140°
Bucket rotation	180°
Stabilizer spread (lowered position)	1778 mm 70 in.
Stabilizer spread (raised position)	1407 mm 55.4 in.

DIMENSIONS & WEIGHTS

Transport overhang	1078 mm 42.4 in.
Transport height (max.)	1806 mm 71.1 in.
Compatible bucket sizes	9" backhoe bucket
Compatible bucket sizes	12" backhoe bucket
Compatible bucket sizes	16" backhoe bucket
Compatible bucket sizes	18" backhoe bucket

COMPATIBLE BUCKET SIZES

TYM's multi-purpose buckets are capable of bulldozing, scraping, loading, metering, moving, and clamping material.

Small_09

Small_12

Small_16

Small_18



Upgrades for the Series 2, 2500

Complement the capabilities of your TYM tractor with compatible accessories and options.

Accessories



Options

Tire	R3 Turf Tires	F 23x8.50 - 12	R 33x12.50-16.5
Tire	R1 Agricultural Tires	F 6 - 12	R 9.5-16
Tire	R4 Industrial Tires	F 23x8.50 - 12	R 12-16.5



Designed for your world

TYM creates tractors that bring together alluring form, advanced function and accessible value. Through Korean expertise in design, engineering and manufacturing, the company helps owners overcome every obstacle as they shape the world around them.

Headquartered in Korea with distribution across North America, Europe, and Asia, and assembly operations in the USA, TYM has been empowering customers for over 70 years.

www.tym.world