


# T554C

Compact, Series 3  
55.9 hp



# A compact tractor setting new standards in productivity and efficiency

This high-performance tractor makes a clear impact without compromising its maneuverability. With exceptional power packed into a compact-sized frame, the T554C redefines what a modern compact tractor can do for you and your property.



1. PTO cruise control



3. 2 sets of rear remote valves



5. All-season cab



2. Projection head lamps



4. Independent rear PTO switch



6. Joystick control for front-end loader





### High efficiency, 4-cylinder Yanmar diesel engine

The Japanese-made Yanmar engine delivers more torque with fewer revs than competitors in its class, significantly maximizing fuel efficiency. Its advanced liquid cooling system warms up the engine quickly and stabilizes temperature more effectively while the tractor is in operation.



### Enhanced attachment controls for efficiency

To boost efficiency, this tractor features controls designed to expedite completion. Two sets of rear remote valves allow the operator to manage various attachments directly from the station, minimizing manual position adjustments. A dial or knob controls lowering speed, while draft control levers regulate depth for optimal ground engagement.



### Interior detailing to promote operator comfort

Activate core functions such as the PTO on/off switch easily from the main console. Quickly receive alerts and diagnostic information via the digital display. The operator platform features a spacious and ergonomic seat and a flat floor with a rubber mat to enhance comfort during entry, exit, and driving.



### Durable, shock absorbing axle configuration

The heavy-duty 4WD front axle enables the tractor to lift heavy loads and tow large attachments while absorbing shock and maintaining stability. Powerful hydraulics support the power steering system, which uses a dual-action mechanism with a hydraulic cylinder and tandem-type hydraulic pump.



### Factory installed joystick controls

The joystick controls come installed from the factory, so you can put the tractor to work as soon as it is delivered. Factory installation ensures that gears are configured perfectly and controls are positioned ergonomically.

# Technical specifications

ENGINE	
Engine manufacturer	Yanmar 4TNV86CT
Type	Turbo Charger
Gross engine power	55.9 hp   41.1 kW
PTO power	45.6 hp   33.5 kW
Rated engine speed	2800 rpm
No. of cylinders	4
Displacement	127.6 cu. in.   2091 cc
Air cleaner	Dual dry
Alternator	12V, 70A
Fuel system	CRDI
POWERTRAIN	
Transmission type	Synchro-Shuttle
No. of speeds	F16 x R16
Max. traveling speed	18.4 mph   29.7 km/h
Brakes	Wet disc
Steering	Hydrostatic
Clutch	Dry single plate
CAPACITIES	
Fuel tank	17.0 gal   60 L
Coolant	9 qt   8.5 L
Crankcase	7.1 qt   6.7 L
Transmission/Hydraulics system	9.2 gal   34.8 L
Front axle	10.5 qt   9.9 L

PTO	
PTO type	Independent
PTO control	Electric/Hydro
PTO rear	540 rpm
HYDRAULIC SYSTEM	
Pump type	Dual gear pump
Implement flow	9.5 gpm   35.7 L/min
Steering flow	4.6 gpm   17.3 L/min
Total flow	14.1 gpm   52.9 L/min
Category, 3-point hitch	I
Hitch lift capacity	3314 lb   1503 kg
Hitch lift capacity at 24 inches behind link ends	2945 lb   1336 kg
Lift control type	Position/Draft
No. of standard remote valves	2
DIMENSIONS & WEIGHTS	
Overall length with 3-point hitch	141.3 in.   3590 mm
Overall width	63.8 in.   1620 mm
Wheelbase	76.2 in.   1935 mm
Height to top of cabin	99.6 in.   2530 mm
Height to top of ROPS	102.1 in.   2594 mm
Min. ground clearance	13.8 in.   350 mm
Min. turn radius with brakes	131.9 in.   3352 mm
Min. turn radius without brakes	150.4 in.   3820 mm
Weight with cab	4233 lb   1920 kg
Weight with ROPS	1730 lb   3814 kg
STANDARD TIRES	
R1 Agricultural - Front	Farm Specialist 9.5-16 NHS TL 6PR
R1 Agricultural - Rear	Farm Specialist 13.6-26 NHS TL 6PR
R3 Turf - Front	Multi-Trac CS 27x10.50-15 NHS TL 4PR
R3 Turf - Rear	Multi-Trac CS 44x18.00-20 NHS TL 4PR
R4 Industrial - Front	Trac Chief 12-16.5 NHS TL 6PR
R4 Industrial - Rear	Xtra Grip 17.5L-24 NHS TL 6PR

# TX55 Front-End Loader

## Attachments

The TX55 front-end loader takes advantage of the power and durability of TYM compact tractors. Ideal for tasks that require more strength, this front-end loader can help you get your tasks done more efficiently.

Lift height	109.1 in.   2770 mm
Lift capacity at pivot point (max. height)	2478 lb   1124 kgf
Bucket capacity	13.8 cu. ft   0.39 cu. m

CAPACITIES & REACH	
Lift height	109.1 in.   2770 mm
Max. lift height under level bucket	99.2 in.   2519 mm
Clearance with bucket dumped	80.8 in.   2052 mm
Reach at maximum lift height	18.6 in.   472 mm
Max. dump angle	48°
Reach with bucket on ground	73.3 in.   1863 mm
Max. rollback angle	35°
Digging depth	5.1 in.   130 mm
Lift capacity at pivot point (max. height)	2478 lb   1124 kgf
Breakout force at ground level, pivot pins	4938 lb   2240 kgf
Bucket rollback force at ground line	4268 lb   1936 kgf
Bucket capacity	13.8 cu. ft   0.39 cu. m
Self leveling	NA
Relief valve setting (loader control valve)	2489 psi   175 kg/sq. cm
Compatible bucket sizes	66" Front-end loader bucket



DIMENSIONS & WEIGHTS	
Overall height in carry position	56.9 in.   1445 mm
Depth of Attachment (to the back of the inner shell)	22.8 in.   579 mm
Height of Attachment	21.9 in.   557 mm
Length of Attachment (to pivot pin)	29.8 in.   758 mm
Weight of boom & quick attach mechanism (1)	564.4 lb   256 kg
Weight of mounting frame (2)	348.3 lb   158 kg
Weight of bucket (3)	348 lb   158 kg
Loader total weight (1+2+3)	1261 lb   572 kg
Lift cylinder	2.4 × 1.4 in.   60 × 35 mm
Bucket cylinder	2.4 × 1.4 in.   60 × 35 mm
Attachment used for specification	72 in.   1830 mm

CYCLE TIMES	
Boom raising time	5.4 sec
Boom lowering time	4.6 sec
Bucket rollback time	3.6 sec
Bucket dumping time	5.0 sec

COMPATIBLE BUCKET SIZES	
TYM's multi-purpose buckets are capable of bulldozing, scraping, loading, metering, moving, and clamping material.	
72" Front-End Loader bucket	

# Upgrades for the Series 3, T554C

Complement the capabilities of your TYM tractor with compatible accessories and options.

## Accessories

Auxiliary hydraulic kit

BHPAD200 Street Pads

Turbo icing protection kit

Front counterweights

T85A Mechanical Thumb



## Options

Tire	R1 Agricultural Tires	F Farm Specialist 9.5 - 16 NHS TL 6PR	R Farm Specialist 14.9-24 NHS TL 6PR
Tire	R3 Turf Tires	F Multi - Trac CS 27x10.50 - 15 NHS TL 4PR	R Multi-Trac CS 44x18.00-20 NHS TL 4PR
Tire	R4 Industrial Tires	F Trac Chief 12 - 16.5 NHS TL 6PR	R Xtra Grip 16.9-24 NHS TL 6PR



# Designed for your world

TYM creates tractors that bring together alluring form, advanced function and accessible value. Through Korean expertise in design, engineering and manufacturing, the company helps owners overcome every obstacle as they shape the world around them.

Headquartered in Korea with distribution across North America, Europe, and Asia, and assembly operations in the USA, TYM has been empowering customers for over 70 years.

[www.tym.world](http://www.tym.world)