

# T69

Compact Utility, Series 5  
68 PS



# A compact utility tractor that combines the latest technology with function

The T69 is the result of TYM's decades-long experience in the agricultural equipment industry and the embodiment of TYM's philosophy on technology, design, and agriculture.



1. Tiger face front fascia



3. Electronic organ-type pedal



4. LED interior lighting



5. Side-rear LED lamp



6. External hitch control buttons



### High-powered Deutz engine

Built with precision German engineering, Deutz engines offer high power and torque, even at low RPMs. Their longer lifespans and high reliability make them an ideal choice to boost productivity.



### Wireless charger, cup warmer & cooler

The wireless smartphone charger and cup warmer and cooler provide comfort during long hours of work. (Available on select models only)



### 6-port external rear remotes and hydraulic top link

2 separate remotes for the top link means that all 6 external rear remotes can be used to mount a variety of attachments. External top link buttons make attaching and detaching attachments easy. (Available on select models only)



### BOSCH electronic hydraulic control system

The German-engineered BOSCH electronic hydraulic control system allows for easy control of the attachments and hydraulic functions like quick turns, horizontal auto-level, and sensitivity controls. (Available on select models only)



### Comfortable suspension seat

Comfort suspension seats provide excellent ride quality and minimizes fatigue during long hours of operation.



### Sun visor

The sun visor ensures maximum visibility by preventing sun glare during daytime operation. (Available on select models only)

# Technical specifications

| ENGINE                         |                         |
|--------------------------------|-------------------------|
| Engine manufacturer            | Deutz TCD2.9L4          |
| Type                           | Turbo engine            |
| Gross engine power             | 68 PS   50 kW           |
| PTO power                      | 61 PS   45 kW           |
| Rated engine speed             | 2200 rpm                |
| No. of cylinders               | 4                       |
| Displacement                   | 2925 cc   178.4 cu. in. |
| Air cleaner                    | Dry                     |
| Air cleaner                    | 건식                      |
| Fuel system                    | CRDI                    |
| POWERTRAIN                     |                         |
| Transmission type              | Power shuttle           |
| No. of speeds                  | F24 × R24               |
| Max. traveling speed           | 40 km/h   24.8 mph      |
| Brakes                         | Wet disc                |
| Steering                       | Hydrostatic             |
| Clutch                         | Dry disc                |
| CAPACITIES                     |                         |
| Fuel tank                      | 72 L   19.02 gal        |
| Coolant                        | 10 L   10.6 qt          |
| Crankcase                      | 8 L   8.5 qt            |
| Transmission/Hydraulics system | 42 L   11 gal           |
| Front axle                     | 16.3 L   4.3 gal        |

| PTO                                               |                                                     |
|---------------------------------------------------|-----------------------------------------------------|
| PTO type                                          | Independent                                         |
| PTO control                                       | Electric/Hydro                                      |
| PTO rear                                          | 540/750/1000 rpm                                    |
| HYDRAULIC SYSTEM                                  |                                                     |
| Pump type                                         | Gear pump                                           |
| Implement flow                                    | 39.1 L/min   10.3 gpm                               |
| Steering flow                                     | 22 L/min   5.8 gpm                                  |
| Total flow                                        | 61.1 L/min   16.1 gpm                               |
| Category, 3-point hitch                           | Cat 2                                               |
| Hitch lift capacity                               | 1964 kg   4329.9 lb                                 |
| Hitch lift capacity at 24 inches behind link ends | 1433 kg   3159 lb                                   |
| Lift control type                                 | Position/Draft                                      |
| No. of standard remote valves                     | 6                                                   |
| DIMENSIONS & WEIGHTS                              |                                                     |
| Overall length with 3-point hitch                 | 3695 mm   145.47 in.                                |
| Overall width                                     | 1840 mm   72.44 in.                                 |
| Wheelbase                                         | 2155 mm   84.84 in.                                 |
| Height to top of ROPS                             | -                                                   |
| Height to top of cabin                            | 2560 mm   100.78 in.                                |
| Min. ground clearance                             | 420 mm   16.53 in.                                  |
| Min. turn radius with brakes                      | (L) 3070 mm   120.87 in. / (R) 2970 mm   116.93 in. |
| Min. turn radius without brakes                   | (L) 3930 mm   154.72 in. / (R) 3840 mm   151.18 in. |
| Track width                                       | F: 1460 mm / R: 1450 mm                             |
| Weight with cab                                   | 2615 kg   5765 lb                                   |
| Weight with ROPS                                  | -                                                   |
| STANDARD TIRES                                    |                                                     |
| Agricultural - Front                              | 11.2-20                                             |
| Agricultural - Rear                               | 14.9-30                                             |

# LX754 Front-End Loader

## Attachments

The TYM LX754 front-end loader provides enhanced lift capabilities to the powerful line of TYM tractors. Compatible with the T59, T69, and T76, the LX754 offers impressive lift height and capacity to help you accomplish heavy-duty tasks.

|                                            |                     |
|--------------------------------------------|---------------------|
| Lift height                                | 3169 mm   124.8 in. |
| Lift capacity at pivot point (max. height) | 1279 kgf   2820 lb  |
| Self leveling                              | Available           |

| CAPACITIES & REACH                          |                             |
|---------------------------------------------|-----------------------------|
| Lift height                                 | 3169 mm   124.8 in.         |
| Max. lift height under level bucket         | 2913 mm   114.7 in.         |
| Clearance with bucket dumped                | 2270 mm   89.4 in.          |
| Reach at maximum lift height                | 247 mm   9.7 in.            |
| Max. dump angle                             | 75°                         |
| Reach with bucket on ground                 | 2100 mm   82.7 in.          |
| Max. rollback angle                         | 49°                         |
| Digging depth                               | 205 mm   8.1 in.            |
| Lift capacity at pivot point (max. height)  | 1279 kgf   2820 lb          |
| Breakout force at ground level, pivot pins  | 2093 kgf   4614 lb          |
| Bucket rollback force at ground line        | 1449 kgf   3194 lb          |
| Self leveling                               | Available                   |
| Relief valve setting (loader control valve) | 175 kg/sq. cm   2489 psi    |
| Compatible bucket sizes                     | 66" Front-end loader bucket |



| DIMENSIONS & WEIGHTS                                 |                            |
|------------------------------------------------------|----------------------------|
| Overall height in carry position                     | 1910 mm   75.2 in.         |
| Depth of Attachment (to the back of the inner shell) | 579 mm   22.8 in.          |
| Height of Attachment                                 | 563 mm   22.2 in.          |
| Length of Attachment (to pivot pin)                  | 861 mm   33.9 in.          |
| Weight of boom & quick attach mechanism (1)          | 359 kg   791 lb            |
| Weight of mounting frame (2)                         | 272 kg   600 lb            |
| Weight of bucket (3)                                 | 168 kg   370 lb            |
| Loader total weight (1+2+3)                          | 799 kg   1761 lb           |
| Lift cylinder                                        | 70 × 40 mm   2.8 × 1.4 in. |
| Bucket cylinder                                      | 60 × 35 mm   2.4 × 1.4 in. |
| Attachment used for specification                    | 1830 mm   72.0 in.         |
| CYCLE TIMES                                          |                            |
| Boom raising time                                    | 6.5 sec                    |
| Boom lowering time                                   | 4.7 sec                    |
| Bucket rollback time                                 | 3.5 sec                    |
| Bucket dumping time                                  | 4.5 sec                    |

# Upgrades for the Series 5, T69

Complement the capabilities of your TYM tractor with compatible accessories and options.

## Accessories

Front counterweights





# Designed for your world

TYM creates tractors that bring together alluring form, advanced function and accessible value. Through Korean expertise in design, engineering and manufacturing, the company helps owners overcome every obstacle as they shape the world around them.

Headquartered in Korea with distribution across North America, Europe, and Asia, and assembly operations in the USA, TYM has been empowering customers for over 70 years.

[www.tym.world](http://www.tym.world)