

T3025

Compact, Series 3
24 hp



A robust compact tractor fit for challenges of all sizes

The T3025 tractor is designed for peak performance through versatility and durability. Offering customizable options throughout, this mid-sized Series 3 compact tractor helps you achieve your goals in applications of varying intensities.



1. New iconic hood



3. Toolbox



2. Comfortable suspension seat



4. Responsive forward/reverse HST



5. High-capacity fuel tank



6. High visibility instrumental panel



Factory-installed joystick

The standard loader joystick helps perform various tasks. By installing a 3rd function kit as needed, it enables even more diverse operations, such as grapple work.



Cruise control

The cruise control feature allows you to set and maintain the engine RPM regardless of the tractor's load conditions.



Lift more

Don't let the size fool you. The T3025 ROPS offers 3,307lb of hitch lift capacity of and 2,200lb of bucket lift capacity.



TYM power

Our TYM diesel is not just smooth, quiet and Tier 4 Certified. It puts out 24 engine hp and 21 PTO hp. Plus it's covered by our 6-year powertrain warranty.



Simple PTO

The Power Take Off (PTO) switch is designed to engage and disengage easily. This will help you with smoother operation and less jerking when using attachments.



Control

The ergonomic joy-stick allows for better control for multiple functions, reducing muscle strain during long hours in the field.

Technical specifications

ENGINE	
Engine manufacturer	TYM T1700N6
Type	Natural aspiration
Gross engine power	24 hp 18 kW
PTO power	21 hp 15.7 kW
Rated engine speed	2100 rpm
No. of cylinders	3
Displacement	104.5 cu. in. 1714 cc
Air cleaner	Dry element
Alternator	12V, 50A
Fuel system	IDI
POWERTRAIN	
Transmission type	2515R: Synchromesh 2515H: HST
No. of speeds	2515R: F12 x F12 2515H: 3-Range
Max. traveling speed	2515R: 11.7 mph 18.8 km/h 2515H: 16.7 mph 26.8 km/h
Brakes	Wet, Multi disc
Steering	Hydrostatic
Clutch	Dry single plate / N/A
CAPACITIES	
Fuel tank	8.7 gal 33 L
Coolant	5.3 qt 5 L
Crankcase	4.5 qt 4.3 L
Transmission/Hydraulics system	8.9 gal 34 L (Synchro) 9.8 gal 37 L (HST)
Front axle	6.8 qt 6.4 L

PTO	
PTO type	Independent
PTO control	Electric/Hydro
PTO rear	540 rpm
HYDRAULIC SYSTEM	
Pump type	Dual gear pump
Implement flow	7.5 gpm 28.4 L/min
Steering flow	4.0 gpm 15.1 L/min
Total flow	11.5 gpm 43.5 L/min
Category, 3-point hitch	I
Hitch lift capacity	3307 lb 1500 kg
Hitch lift capacity at 24 inches behind link ends	2425 lb 1100 kg
Lift control type	Position
No. of standard remote valves	Loader: 4 / Rear: 0 (Optional, up to 4)
DIMENSIONS & WEIGHTS	
Overall length with 3-point hitch	121 in. 3071 mm
Overall width	56.3 in. 1430 mm
Wheelbase	65.7 in. 1670 mm
Height to top of ROPS	97.2 in. 2471 mm
Min. ground clearance	14.4 in. 366 mm
Min. turn radius with brakes	-
Min. turn radius without brakes	105.5 in. / 2680 mm
Weight with ROPS	1347 kg 2969.6 lb
STANDARD TIRES	
R1 Agricultural - Front	8-16
R1 Agricultural - Rear	12.4-24
R3 Turf - Front	27x8.5-15
R3 Turf - Rear	41x14.00
R4 Industrial - Front	10-16.5
R4 Industrial - Rear	420/70-24

Upgrades for the Series 3, T3025

Complement the capabilities of your TYM tractor with compatible accessories and options.

Accessories



Options

Tire	R1 Agricultural Tires	F 8.0 - 16	R 12.4-24
Tire	R4 Industrial Tires	F 25x8.50 - 14	R 15x19.5



Designed for your world

TYM creates tractors that bring together alluring form, advanced function and accessible value. Through Korean expertise in design, engineering and manufacturing, the company helps owners overcome every obstacle as they shape the world around them.

Headquartered in Korea with distribution across North America, Europe, and Asia, and assembly operations in the USA, TYM has been empowering customers for over 70 years.

www.tym.world