


# K58P

Compact, Series 3  
58 ps



# Packed with features to help accomplish your goals


Centered around its powerful 58 PS turbo engine and functionality features, the K58P delivers value and performance. The enhanced hydraulic packages provides 6 ports on the front as well as the rear to take advantage of a wide range of implements.



1. High-quality seat with armrests



2. Power shuttle



3. De-clutch



4. Tilt steering wheel



5. Rear external implement control



6. Electronic lift control



#### 4-cylinder high-output TYM diesel engine

Equipped with a powerful 4-cylinder engine, the tractor maintains a compact size while boasting a similar output to a medium-sized tractor. The durable body and efficient engine combine to efficiently and productively accomplish tasks where a medium-sized tractor is needed. This eco-friendly engine meets Stage-V emissions standards.



#### Deluxe cabin with AC and heater

Standard AC and heater and helps operators work comfortably regardless of the season. It also increases the work efficiency by increasing visibility.




#### Door catch

The convenient door catch makes opening and closing the door smooth.




#### Seat with armrest

The comfortable driver's seat with armrests reduces fatigue during long operations.



#### High-capacity fuel tank

High-capacity fuel tanks allow long operating times without refueling and improves engine fuel efficiency.



#### 6-port rear external hydraulic valve

The 6-port rear external hydraulic valves allows for a wide variety of implements to be installed. This allows for easy rotary tilling, plowing, and transportation of cargo with the tractor.

# Technical specifications

ENGINE	
Engine manufacturer	TYM A2300T
Type	Turbocharger
Gross engine power	58 ps
PTO power	48 ps   35 kW
Rated engine speed	2600 rpm
No. of cylinders	4
Displacement	139.56 cu. in.   2287 cc
Air cleaner	Dry Element
Alternator	12V-70A
Fuel system	Indirect Injection
POWERTRAIN	
Transmission type	Synchro
No. of speeds	F24 x R24
Max. traveling speed	20.39 mph   32.83 km/h
Brakes	Wet Disc
Steering	Hydrostatic
Clutch	Wet Disc
CAPACITIES	
Fuel tank	15.32 gal   58 L
Coolant	6.23 qt   5.9 L
Crankcase	4.75 qt   4.5 L
Transmission/Hydraulics system	11.62 gal   44 L
Front axle	7.39 qt   7.0 L

PTO	
PTO type	Independent
PTO control	Electric/Hydro
PTO rear	540/750/1000
HYDRAULIC SYSTEM	
Pump type	Gear Pump
Implement flow	11.41 gpm   43.2 lpm
Steering flow	5.13 gpm   19.44 lpm
Total flow	16.54 gpm   62.64 lpm
Category, 3-point hitch	Cat 2
Hitch lift capacity	4246.10 lb   1926 kg
Hitch lift capacity at 24 inches behind link ends	3013.71 lb   1367 kg
Lift control type	Position, Draft, TBS
No. of standard remote valves	6
DIMENSIONS & WEIGHTS	
Overall length with 3-point hitch	134.64 in.   3420 mm
Overall width	69.48 in.   1765 mm
Wheelbase	78.74 in.   2000 mm
Height to top of ROPS	99.01 in.   2515 mm
Min. ground clearance	16.92 in.   430 mm
Track width	F: 1340 mm / R: 1355 mm
Min. turn radius with brakes	103.14 in.   2620 mm
Min. turn radius without brakes	124.80 in.   3170 mm
Weight with ROPS	4905.28 lb   2225 kg
STANDARD TIRES	
Agricultural - Front	9.5 - 20
Agricultural - Rear	14.9 - 28

# KJL58 Front-End Loader

## Attachments

The TYM KJL58 front-end loader raises the bar in material handling and productivity. Providing an impressive lift height and capacity, the KJL58 complements the power and performance of compatible TYM K58P compact tractors.



Lift height	122.6 in. / 3115 mm
Lift capacity	2072 lb / 940 kgf
Self leveling	Available

CAPACITIES & REACH	
Lift height	122.6 in.   3115 mm
Max. lift height under level bucket	114.3 in.   2902 mm
Clearance with bucket dumped	95.4 in.   2422 mm
Reach at maximum lift height	6.6 in.   168 mm
Max. dump angle	80°
Reach with bucket on ground	84.8 in.   2155 mm
Max. rollback angle	50°
Digging depth	5.1 in.   130 mm
Lift capacity	2072 lb   940 kgf
Breakout force at ground level, pivot points	2961 lb   1343 kgf
Bucket rollback force at ground line	3430 lb   1556 kgf
Self leveling	Available
Relief valve setting (Loader control valve)	2347 psi   165 kg/sq. cm

DIMENSIONS & WEIGHTS	
Overall height in carry position	65.7 in.   1670 mm
Depth of Attachment (to the back of the inner shell)	21.6 in.   549 mm
Height of Attachment	20.1 in.   510 mm
Length of Attachment (to pivot point)	26.2 in.   665 mm
Weight of boom & quick attach mechanism (1)	525 lb   238 kg
Weight of mounting frame (2)	187 lb   85 kg
Weight of bucket (3)	238 lb   108 kg
Loader total weight (1+2+3)	950 lb   431 kg
Lift cylinder	2.8x1.6 in.   60x40 mm
Bucket cylinder	2.8x1.6 in.   60x35 mm
Attachment used for specification	61.8 in.   1570 mm

CYCLE TIMES	
Boom raising time	4.5 sec
Boom lowering time	3.1 sec
Bucket rollback time	2.2 sec
Bucket dumping time	3.0 sec

### COMPATIBLE BUCKET SIZES

TYM's multi-purpose buckets are capable of bulldozing, scraping, loading, metering, moving, and clamping material.

66" Front-End Loader bucket



# Designed for your world

TYM creates tractors that bring together alluring form, advanced function and accessible value. Through Korean expertise in design, engineering and manufacturing, the company helps owners overcome every obstacle as they shape the world around them.

Headquartered in Korea with distribution across North America, Europe, and Asia, and assembly operations in the USA, TYM has been empowering customers for over 70 years.

[www.tym.world](http://www.tym.world)