


2500L

Sub-Compact, Series 2
24 hp



A versatile sub-compact tractor for projects of all sizes

The T2026 (2500L) is a highly maneuverable sub-compact tractor that offers both versatility and power, and perfect for everyone from hobbyists to groundskeepers. Experience the convenience of a ride-on mower with the capabilities of a full-size tractor.



1. New iconic hood



3. Ergonomic lever



2. Sub shift (3 ranges, T2026 (2500HL))



4. Highly responsive forward & reverse HST (T2026 (2500HL))



5. PTO lever



6. 2 port rear hydraulic control (optional)




Eco-friendly 3-cylinder Stage V TYM engine

The T2026 (2500L) is equipped with a naturally aspirated engine designed and manufactured by TYM. While designed to be fuel efficient and eco-friendly, the TYM engine makes no compromise on performance and reliability.



High-visibility instrumental panel

Be fully aware of your working conditions. The clear instrumental panel on TYM tractors enables you to keep track of essential information such as speed, fuel, and tractor status at all times.



Four-wheel drive

Standard four-wheel drive on these tractors result in higher work efficiency, even in the most challenging environments.



Foldable ROPS

The Roll Over Protective Structure (ROPS) of the tractor is designed to be folded, allowing for easy storage in garages, sheds, and other low-ceiling structures.



Cruise control (HST)

The cruise control function allows you to set and maintain engine RPM, regardless of the tractor's load conditions.



High ground clearance

An impressive ground clearance of 307mm makes it possible for to operate without difficulty on rocky or uneven terrain

Technical specifications

ENGINE	
Engine Manufacturer	TYM T1100N2
Type	Natural aspiration
Gross engine power	24 hp 18 kW
PTO power	2500L: 20.7 hp 15.5 kW 2500HL: 18 hp 13.5 kW
Rated engine speed	2800 rpm
No. of cylinders	3
Displacement	1175 cc 71.7 cu. in.
Air cleaner	Dry element
Alternator	12V, 60A
Fuel system	Water-cooled diesel

POWERTRAIN	
Transmission type	2500L: Constant mesh 2500HL: HST
No. of speeds	2500L: F6 x R2 / F9 x R3 2500HL: 2 Range / 3 Range
Max. traveling speed	2500L 21.9 km/h 13.6 mph 22.6 km/h 14 mph 2500HL 24.6 km/h 15.3 mph 26.2 km/h 16.3 mph
Brakes	Wet, Multi disc
Steering	Hydrostatic
Clutch	Dry single plate

CAPACITIES	
Fuel tank	23 L 6.0 gal
Coolant	5 L 5.3 qt
Crankcase	3.2 L 3.4 qt
Transmission/Hydraulics system	10 L 2.6 gal
Front axle	3 L 3.2 qt

PTO	
PTO type	Live
PTO control	Manual
PTO rear	Rear: 540/1000 rpm Mid: 2500 rpm

HYDRAULIC SYSTEM	
Pump type	Gear pump
Implement flow	17.6 L/min 4.7 gpm
Steering flow	12.6 L/min 3.3 gpm
Total flow	30.2 L/min 8.0 gpm
Category, 3-point hitch	I
Hitch lift capacity	512 kg 1129 lb
Hitch lift capacity at 24 inches behind link ends	328 kg 724 lb
Lift control type	Position
No. of standard remote valves	Optional (2)


DIMENSIONS & WEIGHTS	
Overall length with 3-point hitch	3124 mm 123 in.
Overall width	1419 mm 55.9 in.
Wheelbase	1672 mm 65.8 in.
Height to top of ROPS	F-ROPS: 2102 mm 82.8 in. ROPS: 2330 mm 91.7 in.
Height to top of Cabin	-
Min. ground clearance	417 mm 16.4 in.
Min. turn radius with brakes	2700 mm 106.3 in.
Min. turn radius without brakes	2240 mm 88.2 in.
Weight with ROPS	1: F-ROPS: 1022 kg / ROPS: 988 kg 2: F-ROPS: 985 kg / ROPS: 962 kg
Weight with cab	-

STANDARD TIRES	
R1 Agricultural - Front	1: 6-12 4PR 2: 6-12 4PR 3: 7-16 6PR 4: 200/70R16
R1 Agricultural - Rear	1: 9.5-16 6PR 2: 9.5-18 8PR 3: 11.2-20 8PR 4: 320/70R20
R3 Turf - Front	25x8.50-12
R3 Turf - Rear	33x12.50-16.5
R4 Industrial - Front	23x8.50-12
R4 Industrial - Rear	33x12.50-16.5

BM60E Mid-Mount Mower

Attachments

Built with 60-inch working width cutting deck and 5.12-inch transport height, the TYM BM60E mid-mount mower attachment is designed to optimize your cutting time and improve cut quality.



PERFORMANCE

No. of blades	3 EA
Blade Velocity	3363 fpm
Blade Length	528.3 mm 20.8 in.
Power Rating	13.4-14.9 kW (18-20 hp)

DIMENSIONS & WEIGHTS

Working width	1524 mm 60 in.
Length	38.2 mm 1.5 in.
Width	74.3 mm 2.92 in.
Height	7.2 mm 0.28 in.
Weight	123.4 kg 272 lb
Cutting height	25.4 - 101.6 mm 1 - 4 in.
Transport height	129.5 mm 5.1 in.

GENERAL

Type	Side discharge
Mounting method	Parallel linkage
Lift linkage type	Lower link lift
Adjustment of increment	Dial gauge
Dial gauge hole	7 EA
Dial gauge gab between hole	12.7 mm 0.5 in.
Dial gauge total gab	76.2 mm (3 in.)
Universal joint	Ø21.6 × 525 L
Wheel	4 EA
Assistant wheel	1 EA
Belt	V-Belt
Color	RED
Deck thickness	3.3 mm 0.13 in.

Upgrades for the Series 2 2500L

Complement the capabilities of your TYM tractor with compatible accessories and options.

ACCESSORIES



OPTIONS

Tire	R3 Turf Tires	F 23x8.50 - 12	R 33x12.50-16.5
Tire	R1 Agricultural Tires	F 7 - 16	R 11.2-20
Tire	R4 Industrial Tires	F 25x8.50 - 14	R 14-17.5



Designed for your world

TYM creates tractors that bring together alluring form, advanced function and accessible value. Through Korean expertise in design, engineering and manufacturing, the company helps owners overcome every obstacle as they shape the world around them.

Headquartered in Korea with distribution across North America, Europe, and Asia, and assembly operations in the USA, TYM has been empowering customers for over 70 years.

www.tym.world