

A powerful utility tractor designed to conquer the most demanding tasks

The T115 is a powerful tractor engineered to meet the demands of modern agriculture, combining operational efficiency with robust performance. Its enhanced lift capacity and updated hydraulic top link handle heavy-duty tasks with ease, while telematics enables efficient farm management.







1. Air-ride full suspension seat



2. Side view mirrors



3. Ergonomic operational control center







5. Organ pedal

6. Telescopic top link



Deutz engine for exceptional productivity

The T115 is fitted with the TCD 3.6 L4, Deutz Common Rail Engine with Bosch's advanced electronic hydraulic control system, which excels in high-intensity tasks. This engine delivers exceptional power and torque at a lower rpm, promoting durability and productivity over a longer lifespan.



Premium cabin

Enjoy panoramic views, easy entry and exit through both side doors, and a suite of premium cabin amenities that boost productivity while prioritizing safety and well-being.



Durable, shock-absorbing axle configuration

The rugged front axle of the T115 excels in tough conditions, consistently offering robust load-bearing and long-lasting inboard planetary gear design. It also features a generous 50-degree steering angle and optimized geometry for precise control, maneuverability, and reduced tire wear.



High-capacity 3-point hitch

Equipped with a high-capacity 3-point hitch, offering an optional 3900 kg lift capacity and designed to handle heavy loads and a variety of attachments, this tractor ensures secure and optimal performance for your tools.



Full LED Support

LED turn signals and work lamps for enhanced visibility in even the darkest of environments.



TFT LCD rear monitor system

Utilize the user-friendly monitor to access vital information, including dual cameras (front and/or rear), radio, phone, multimedia, tractor data, and various settings.

Technical specifications

ENGINE	
Engine manufacturer	Deutz TCD 3.6L4
Туре	Turbo charger
Gross engine power	111 hp 83 kW
PTO power	109 hp 80 kW
Rated engine speed	2200 rpm
No. of cylinders	4
Displacement	3621 cc 221 cu. in.
Air cleaner	Dual dry
Alternator	12V, 120A
Fuel system	CRDI
POWERTRAIN	
Transmission type	Power shuttle & Hi-Lo shift
Transmission type No. of speeds	Power shuttle & Hi-Lo shift F32 × R32 w/Creep
No. of speeds	F32 \times R32 w/Creep
No. of speeds Max. traveling speed	F32 × R32 w/Creep 37.1 km/h 23 mph
No. of speeds Max. traveling speed Brakes	F32 × R32 w/Creep 37.1 km/h 23 mph Wet, Multi disc
No. of speeds Max. traveling speed Brakes Steering	F32 × R32 w/Creep 37.1 km/h 23 mph Wet, Multi disc Hydrostatic
No. of speeds Max. traveling speed Brakes Steering Clutch	F32 × R32 w/Creep 37.1 km/h 23 mph Wet, Multi disc Hydrostatic
No. of speeds Max. traveling speed Brakes Steering Clutch CAPACITIES	F32 × R32 w/Creep 37.1 km/h 23 mph Wet, Multi disc Hydrostatic Wet multi-plate
No. of speeds Max. traveling speed Brakes Steering Clutch CAPACITIES Fuel tank	F32 × R32 w/Creep37.1 km/h 23 mphWet, Multi discHydrostaticWet multi-plate110 L 29.1 gal
No. of speeds Max. traveling speed Brakes Steering Clutch CAPACITIES Fuel tank Coolant	F32 × R32 w/Creep 37.1 km/h 23 mph Wet, Multi disc Hydrostatic Wet multi-plate 110 L 29.1 gal 18.1 L 19.1 qt
No. of speeds Max. traveling speed Brakes Steering Clutch CAPACITIES Fuel tank Coolant Crankcase	F32 × R32 w/Creep 37.1 km/h 23 mph Wet, Multi disc Hydrostatic Wet multi-plate 110 L 29.1 gal 18.1 L 19.1 qt 8 L 8.5 qt

Independent
Electric/Hydro
540/540E/1000 rpm (Reversible shaft)
Dual gear pump
54.1 L/min 14.3 gpm
27.0 L/min 7.1 gpm
81.1 L/min 21.4 gpm
II
3309 kg 7295 lb (Optional: 3900 kg 8598 lb)
2722 kg 6008 lb
Position/Draft
6
6
6 4470 mm 176 in.
4470 mm 176 in.
4470 mm 176 in. 2270 mm 89.4 in.
4470 mm 176 in. 2270 mm 89.4 in. 2360 mm 92.9 in.
4470 mm 176 in. 2270 mm 89.4 in. 2360 mm 92.9 in. 2740 mm 107.9 in.
4470 mm 176 in. 2270 mm 89.4 in. 2360 mm 92.9 in. 2740 mm 107.9 in.
4470 mm 176 in. 2270 mm 89.4 in. 2360 mm 92.9 in. 2740 mm 107.9 in. - 460 mm 18.1 in.
4470 mm 176 in. 2270 mm 89.4 in. 2360 mm 92.9 in. 2740 mm 107.9 in. - 460 mm 18.1 in. (L) 3660 mm 144.1 in. / (R) 3670 mm 144.5 in.
4470 mm 176 in. 2270 mm 89.4 in. 2360 mm 92.9 in. 2740 mm 107.9 in. - 460 mm 18.1 in. (L) 3660 mm 144.1 in. / (R) 3670 mm 144.5 in. (L) 4310 mm 169.7 in. / (R) 4350 mm 171.3 in.
4470 mm 176 in. 2270 mm 89.4 in. 2360 mm 92.9 in. 2740 mm 107.9 in. - 460 mm 18.1 in. (L) 3660 mm 144.1 in. / (R) 3670 mm 144.5 in. (L) 4310 mm 169.7 in. / (R) 4350 mm 171.3 in.
4470 mm 176 in. 2270 mm 89.4 in. 2360 mm 92.9 in. 2740 mm 107.9 in. - 460 mm 18.1 in. (L) 3660 mm 144.1 in. / (R) 3670 mm 144.5 in. (L) 4310 mm 169.7 in. / (R) 4350 mm 171.3 in.



Designed for your world

TYM creates tractors that bring together alluring form, advanced function and accessible value. Through Korean expertise in design, engineering and manufacturing, the company helps owners overcome every obstacle as they shape the world around them.

Headquartered in Korea with distribution across North America, Europe, and Asia, and assembly operations in the USA, TYM has been empowering customers for over 70 years.

www.tym.world