

T58

Compact, Series 3
55 PS



A compact tractor that balances power with maneuverability

Take on tough jobs in tight spaces with the T58. This tractor brings you the best features from our compact and utility ranges, balancing high power output with maximized maneuverability.



1. PTO mode switch (OFF, MANUAL, AUTO)



3. Rear external hydraulic valve



5. PTO lever




2. Throttle lever



4. ROPS



6. Joystick control for front-end loader



4-cylinder TYM diesel engine with high output

4-cylinder TYM diesel engine with high output




Superior operator amenities

Amenities such as cup holders and storage space near the operator.



Durable power steering and axle configuration

The heavy duty 4WD front axle allows the tractor to lift heavy loads and tow large implements. Powerful hydraulics support the power steering system, which benefits from a dual action mechanism using a hydraulic cylinder and tandem type hydraulic pump.



3rd function hydraulic valve to enhance attachment capabilities

Allowing for versatile attachment handling, this tractor comes ready with a 3rd function installation kit. It can maximize the use of a bucket attachment with 4-in-1 functionality, including lifting, tilting, dumping, and grappling.



Convenient one-touch hood open

Convenient one-touch hood open

Technical specifications

ENGINE	
Engine manufacturer	TYM T2300T
Type	Turbocharger
Gross engine power	55 PS 40.5 kW
PTO power	44.9 PS 33.0 kW
Rated engine speed	2600 rpm
No. of cylinders	4
Displacement	2287 cc 139.5 cu. in.
Air cleaner	Dual dry
Alternator	12V, 70A
Fuel system	IDI
POWERTRAIN	
Transmission type	Synchro-shuttle
No. of speeds	F8 x R8
Max. traveling speed	26.49 km/h 16.46 mph
Brakes	Wet disc
Steering	Hydrostatic
Clutch	Dry disc
CAPACITIES	
Fuel tank	60 L 17.0 gal
Coolant	7.0 L 7.39 qt
Crankcase	6.4 L 6.8 qt
Transmission/Hydraulics system	35 L 9.2 gal
Front axle	9.9 L 10.5 qt

PTO	
PTO type	Independent
PTO control	Electric/Hydro
PTO rear	540/750/1000 rpm
HYDRAULIC SYSTEM	
Pump type	Dual gear pump
Implement flow	29 L/min 7.66 gpm
Steering flow	16.08 L/min 4.25 gpm
Total flow	45.08 L/min 11.91 gpm
Category, 3-point hitch	Cat 1
Hitch lift capacity	1733 kg 3822 lb
Hitch lift capacity at 24 inches behind link ends	1384 kg 3050.61 lb
Lift control type	Position
No. of standard remote valves	2
DIMENSIONS & WEIGHTS	
Overall length with 3-point hitch	3400 mm 133.9 in.
Overall width	1610 mm 63.4 in.
Wheelbase	1935 mm 76.2 in.
Height to top of ROPS	2490 mm 98 in.
Height to top of cabin	-
Min. ground clearance	340 mm 13.4 in.
Min. turn radius with brakes	(L) 3000 mm 118.11 in. / (R) 3000 mm 118.11 in.
Min. turn radius without brakes	(L) 3190 mm 125.59 in. / (R) 3230 mm 127.17 in.
Weight with ROPS	1980 kg 4365 lb
Weight with cab	-
Track width	F: 1290 mm / R: 1215 mm
STANDARD TIRES	
Agricultural - Front	9.5-16
Agricultural - Rear	13.6-26

LX554CE Front-End Loader

Attachments

The LX554CE front-end loader raises the bar in material handling and productivity. Providing an impressive lift height and capacity, the LX554CE complements the power and performance of its compatible TYM T58 and T58C compact tractors.

Lift height	2834 mm 111.6 in.
Lift capacity at pivot point (max. height)	1200 kgf 2646 lb
Self leveling	Available

CAPACITIES & REACH	
Lift height	2834 mm 111.6 in.
Max. lift height under level bucket	2618 mm 103.1 in.
Clearance with bucket dumped	2618 mm 103.1 in.
Reach at maximum lift height	115 mm 4.5 in.
Max. dump angle	76°
Reach with bucket on ground	1763 mm 69.4 in.
Max. rollback angle	46°
Digging depth	153 mm 6.0 in.
Lift capacity at pivot point (max. height)	1200 kgf 2646 lb
Breakout force at ground level, pivot pins	2282 kgf 5031 lb
Bucket rollback force at ground line	2049 kgf 4517 lb
Self leveling	Available
Relief valve setting (loader control valve)	175 kg/sq. cm 2489 psi
Compatible bucket sizes	66" Front-end loader bucket
DIMENSIONS & WEIGHTS	
Overall height in carry position	1507 mm 59.3 in.
Depth of Attachment (to the back of the inner shell)	549 mm 21.6 in.



Height of Attachment	510 mm 20.1 in.
Length of Attachment (to pivot pin)	665 mm 26.2 in.
Weight of boom & quick attach mechanism (1)	238 kg 525 lb
Weight of mounting frame (2)	95 kg 209 lb
Weight of bucket (3)	114 kg 251 lb
Loader total weight (1+2+3)	447 kg 985 lb
Lift cylinder	60 × 35 mm 2.4 × 1.4 in.
Bucket cylinder	60 × 35 mm 2.4 × 1.4 in.
Attachment used for specification	1570 mm 61.8 in.

CYCLE TIMES	
Boom raising time	6.4 sec
Boom lowering time	3.6 sec
Bucket rollback time	3.2 sec
Bucket dumping time	4.8 sec

COMPATIBLE BUCKET SIZES	
TYM's multi-purpose buckets are capable of bulldozing, scraping, loading, metering, moving, and clamping material.	
66" Front-End Loader bucket	

Upgrades for the Series 3, T58

Complement the capabilities of your TYM tractor with compatible accessories and options.

Accessories

Front counterweights





Designed for your world

TYM creates tractors that bring together alluring form, advanced function and accessible value. Through Korean expertise in design, engineering and manufacturing, the company helps owners overcome every obstacle as they shape the world around them.

Headquartered in Korea with distribution across North America, Europe, and Asia, and assembly operations in the USA, TYM has been empowering customers for over 70 years.

www.tym.world