

2026 Catalog

Series 2

Sub-Compact Tractors
24 - 24.7 hp



For distribution and sales in North American territories

Series 2 Sub-Compact Tractors

The Series 2 tractors are built to take on more demanding tasks—all within a compact frame designed to handle everyday chores and tough

challenges. Use the front-end loader to transport material or the rear hitch for tow-behind attachments to clean up efficiently.



2400

Engine power **Lift capacity**
24 hp | 17.9 kW 1499 lb | 680 kg



2610

Engine power **Lift capacity**
24 hp | 17.9 kW 1499 lb | 680 kg



T264

Engine power **Lift capacity**
24 hp | 18 kW 1534 lb | 696 kg



T25

Engine power **Lift capacity**
24.7 hp | 18.4 kW 1551.2 lb | 703.6 kg



T2025P

Engine power **Lift capacity**
24.7 hp | 18.4 kW 1550 lb | 703 kg

Built to tackle a variety of tasks on your land

The Series 2 tractors have enhanced performance capabilities while maintaining compact frames. Functional design and precision engineering come together to promote productivity, from the Stage V certified engine to the ergonomically configured operator platform. Use a Series 2 tractor to maintain a healthy lawn, build a home garden, take care of yard work, or create a lively home farm. Front-end loader, mid-mount mower and rear hitch linkages enable you to attach a variety of attachments and do more per cycle.

Most popular applications



Arable Farming



Construction



Snow Clearing



Landscaping



All the right features to get the job done



Eco-friendly TYM Tier 4 engine

Equipped with a naturally aspirated engine designed and manufactured by TYM, the tractor is designed to be eco-friendly and fuel-efficient without compromising on performance.



Four-wheel drive

Four-wheel drive comes as a standard for higher work efficiency, even in the most challenging environment.



Cruise control (HST)

The cruise control function allows you to set and maintain engine RPM, regardless of the tractor's load conditions.



High-visibility instrumental panel

Be fully aware of your working conditions. An instrumental panel with high visibility enables you to keep track of essential information such as speed, fuel, and the status of your tractor at any time of the day.



Foldable ROPS

The Roll Over Protective Structure (ROPS) of the tractor is designed to be folded, allowing for easy storage in garages, sheds, and other low-ceiling structures.



Ground clearance

Ground clearance of 307 mm makes operation on rocky or uneven terrain easier than ever before.

2400

A sub-compact tractor for everyone, suitable for projects of every size



1. New iconic hood



2. Comfortable suspension seat



3. Ergonomic lever

Key specifications:

Engine power
24 hp | 17.9 kW

Engine manufacturer
TYM T1100N2

Lift capacity
1499 lb | 680 kg

PTO power
21 hp | 15.7 kW



4. Responsive forward/reverse HST (2400H)



5. PTO lever



6. 2 port rear hydraulic control (optional)

2610


A sub-compact tractor built for everyday efficiency and versatility



1. New iconic hood



2. Comfortable suspension seat



3. Ergonomic lever

Key specifications:

Engine power
24 hp | 17.9 kW

Engine manufacturer
TYM T1100N2

Lift capacity
1499 lb | 680 kg

PTO power
18 hp | 13.5 kW



4. Responsive forward & reverse
HST



5. PTO lever



6. 2 port rear hydraulic control
(optional)

T264

A versatile sub-compact tractor designed for maneuverability



1. Optional loader with high lift capacity



2. PTO on/off switch



3. Dual filter air cleaner



4. Cruise control



5. Foldable ROPS



6. Joystick control for front loader

Key specifications:

Engine power
24 hp | 18 kW

Engine manufacturer
TYM T1100N2

Lift capacity
1534 lb | 696 kg

PTO power
18.3 hp | 13.6 kW




T25

A sub-compact tractor engineered for productivity inside and out



1. 2-range hydrostatic transmission (HST)



2. 3rd function hydraulic valve (optional)



3. 2 USB ports



4. Waterproof Bluetooth speaker



5. Wireless smartphone charger



6. Wide loadspace with toolbox

Key specifications:

Engine power
24.7 hp | 18.4 kW

Engine manufacturer
Yanmar 3TNV80F

Lift capacity
1551.2 lb | 703.6 kg

PTO power
18.3 hp | 13.6 kW

T2025P

A sub-compact tractor engineered for productivity inside and out

Key specifications:

Engine power
24.7 hp | 18.4 kW

Engine manufacturer
Yanmar 3TNV80F-NXDKTFX

Lift capacity
1550 lb | 703 kg

PTO power
18.3 hp | 13.6 kW



1. Mechanical suspension seat



2. Integrated work signal lighting




3. Tool box



4. Easy reach SCV lever



5. High visibility lever



6. Easy oil access

Specification Guide

MODEL	2400	2610	T264	T25
ENGINE				
Engine Manufacturer	TYM T1100N2	TYM T1100N2	TYM T1100N2	Yanmar 3TNV80F
Type	Natural aspiration	Natural aspiration	Natural aspiration	Natural aspiration
Engine power	24 hp 17.9 kW	24 hp 17.9 kW	24 hp 18 kW	24.7 hp 18.4 kW
PTO power	21 hp 15.7 kW	18 hp 13.5 kW	18.3 hp 13.6 kW	18.3 hp 13.6 kW
Rated engine speed	2850 rpm	2850 rpm	2800 rpm	3000 rpm
No. of cylinders	3	3	3	3
Displacement	71.7 cu. in. 1175 cc	71.7 cu. in. 1175 cc	71.7 cu. in. 1175 cc	77.3 cu. in. 1267 cc
Air cleaner	Dry element	Dry element	Single dry	Single dry
Alternator	12V, 60A	12V, 60A	12V, 50A	12V, 40A
Fuel system	IDI	IDI	IDI	IDI
POWERTRAIN				
Transmission type	2400R: Constant Mesh 2400H: HST	HST	HST	HST
No. of speeds	2400R: F6 x R2 2400H: 2-Range	3-Range	Infinite 2-Range	Infinite 2-Range
Max. traveling speed	2400R: 9.9 mph 15.9 km/h 2400H: 12.1 mph 19.4 km/h	17 mph 27.5 km/h	12.9 mph 20.8 km/h	13.7 mph 22 km/h
Brakes	Wet, Multi disc	Wet, Multi disc	Wet disc	Wet disc
Steering	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Clutch	Dry single plate	Dry single plate	Dry single plate	N/A
HYDRAULIC SYSTEM				
Pump type	Dual gear pump	Dual gear pump	Dual gear pump	Single gear pump
Implement flow	4.7 gpm 17.6 L/min	4.65 gpm 17.6 L/min	4.4 gpm 16.6 L/min	4.2 gpm 15.8 L/min
Steering flow	3.3 gpm 12.6 L/min	3.3 gpm 12.6 L/min	2.7 gpm 10.4 L/min	2.8 gpm 10.5 L/min
Total flow	7.9 gpm 30.2 L/min	7.9 gpm 30.2 L/min	7.1 gpm 26.9 L/min	6.9 gpm 26.3 L/min
Category, 3-point hitch	I	I	I	I
Hitch lift capacity	1499 lb 680 kg	1499 lb 680 kg	1534 lb 696 kg	1551.2 lb 703.6 kg
Hitch lift capacity at 24 inches behind link ends	974 lb 442 kg	974 lb 442 kg	1102 lb 500 kg	1229.7 lb 557.8 kg
Lift control type	Position	Position	Position	Position
No. of standard remote valves	Optional (2)	Optional (2)	Optional (1)	1
PTO				
PTO type	Live	Live	Independent	Independent
PTO rear	540/1000 rpm	540/1000 rpm	540 rpm	540 rpm
CAPACITIES				
Fuel tank	6.0 gal 23 L	6.0 gal 23 L	6.6 gal 25 L	6.6 gal 25 L
Coolant	5.3 qt 5 L	5.3 qt 5 L	5.9 qt 5.5 L	3.8 qt 3.6 L
Crankcase	2.9 qt 2.8 L	2.9 qt 2.8 L	4.5 qt 4.3 L	2.9 qt 2.7 L

Transmission/Hydraulics system	3.7 gal 14 L	3.7 gal 14 L	4.7 gal 17.8 L	4.5 gal 17 L
Front axle	3.5 qt 3.3 L	3.5 qt 3.3 L	4.7 qt 4.4 L	4.7 qt 4.5 L
DIMENSIONS & WEIGHTS				
Overall length with 3-point hitch	120.3 in. 3055 mm	122.9 in. 3122 mm	107.8 in. 2740 mm	102.8 in. 2610 mm
Overall width	44.2 in. 1122.7 mm	53.8 in. 1369 mm	52.8 in. 1342 mm	50 in. 1270 mm
Wheelbase	59.1 in. 1502 mm	65.7 in. 1670 mm	58.3 in. 1480 mm	61 in. 1550 mm
Height to top of ROPS	87.3 in. 2219 mm	91.5 in. 2328 mm	89.8 in. 2280 mm	91.3 in. 2320 mm
Height to top of Cabin	-	-	-	-
Min. ground clearance	12.1 in. 307.3 mm	15.1 in. 382 mm	7.7 in. 196 mm	10.2 in. 260 mm
Min. turn radius with brakes	(L) 9.3 ft 2820 mm / (R) 9.2 ft 2790 mm	(L) 9.3 ft 2820 mm / (R) 9.2 ft 2790 mm	98.5 in. 2502 mm	94.1 in. 2390 mm
Min. turn radius without brakes	(L) 9.6 ft 2930 mm / (R) 9.5 ft 2900 mm	(L) 9.6 ft 2930 mm / (R) 9.5 ft 2900 mm	105.5 in. 2682 mm	111.8 in. 2840 mm
Weight with ROPS	1792 lb 813 kg	2106 lb 956 kg	1881 lb 853 kg	2046 lb 928 kg
Weight with cab	-	-	-	-
STANDARD TIRES				
R1 Agricultural - Front	6-12	7-16	-	6-12 4PR
R1 Agricultural - Rear	9.5-16	11.2-20	-	9.5-20 6PR
R3 Turf - Front	23x8.50-12	23x8.50-12	Turf Master 23x8.50-12 NHS TL 4PR	Turf Master 23x8.50-12 NHS TL 4PR
R3 Turf - Rear	33x12.50-16.5	33x12.50-16.5	Multi-Trac CS 33x12.50-16.5 NHS TL 4PR	Multi-Trac CS 33x12.50-16.5 NHS TL 4PR
R4 Industrial - Front	23x8.50-12	23x8.50-12	Trac Chief 23x8.50-12 NHS TL 4PR	Trac Chief 23x8.50-14 NHS TL 4PR
R4 Industrial - Rear	12-16.5	12-16.5	Trac Chief 12-16.5 NHS TL 6PR	36X12.5-15

Specification Guide

MODEL	T2025P
ENGINE	
Engine Manufacturer	Yanmar 3TNV80F-NXDKTFX
Type	Natural aspiration
Engine power	24.7 hp 18.4 kW
PTO power	18.3 hp 13.6 kW
Rated engine speed	3000 rpm
No. of cylinders	3
Displacement	77.3 cu. in. 1267 cc
Air cleaner	Single dry
Alternator	12V, 40A
Fuel system	IDI
POWERTRAIN	
Transmission type	HST
No. of speeds	2
Max. traveling speed	13.57 mph 21.84 km/h
Brakes	Wet disc
Steering	Hydraulic
Clutch	N/A
HYDRAULIC SYSTEM	
Pump type	Single gear pump
Implement flow	4.17 gpm 15.8 L/min
Steering flow	2.77 gpm 10.5 L/min
Total flow	6.94 gpm 26.3 L/min
Category, 3-point hitch	I
Hitch lift capacity	1550 lb 703 kg
Hitch lift capacity at 24 inches behind link ends	254 lb 557.8 kg
Lift control type	Position
No. of standard remote valves	4/2 (1 set)
PTO	
PTO type	Independent
PTO rear	540 rpm
CAPACITIES	
Fuel tank	8.4 gal 32 L
Coolant	3.6 gal 0.95 L
Crankcase	-
Transmission/Hydraulics system	4.49 gal 17 L
Front axle	4.5 L 1.18 gal
DIMENSIONS & WEIGHTS	

Overall length with 3-point hitch	105.11 in. 2670 mm
Overall width	56.29 in. 1430 mm
Wheelbase	61.02 in. 1550 mm
Height to top of ROPS	85.94 in. 2183 mm
Height to top of Cabin	-
Min. ground clearance	10.23 in. 260 mm
Min. turn radius with brakes	102.40 in. 2601 mm
Min. turn radius without brakes	110.23 in. 2800 mm
Weight with ROPS	4865.16 lb 2206.8 kg
Weight with cab	-
STANDARD TIRES	
R1 Agricultural - Front	-
R1 Agricultural - Rear	-
R3 Turf - Front	23x8.5-12
R3 Turf - Rear	33x12.5-16.5
R4 Industrial - Front	23x8.5-14
R4 Industrial - Rear	14-17.5



Designed for your world

TYM creates tractors that bring together alluring form, advanced function and accessible value. Through Korean expertise in design, engineering and manufacturing, the company helps owners overcome every obstacle as they shape the world around them.

Headquartered in Korea with distribution across North America, Europe, and Asia, and assembly operations in the USA, TYM has been empowering customers for over 70 years.

www.tym.world