

T265

Sub Compact, Series 1
24 hp



A versatile sub-compact tractor designed for maneuverability

Get more work done in less time with the T265. This sub-compact tractor balances impressive lift capabilities and high maneuverability to stand out as an all-around multi-tasking machine.



1. Optional loader with high lift capacity



3. Dual filter air cleaner



5. Foldable ROPS



2. PTO on/off switch



4. Cruise control



6. Joystick control for front loader



Ergonomic features for enhanced productivity

A wide operator cabin with a flat floor offers good visibility and ample leg room, promoting comfortable operation. All controls are within arm's reach, including a dial to control the cutting height of the mid-mount implement. The accelerator, brake pedal, differential lock, and parking brake are easily accessible on the floor of the cabin, located precisely where you expect them to be. These features make this tractor easy to operate, even for novice drivers




Simple and effective TYM engine

This tractor comes equipped with the South Korean-made TYM engine and is naturally aspirated. The minimal design and minimized emissions results in a more efficient engine, lowering fuel and maintenance costs.



High-capacity fuel tank for time-intensive work

The high-capacity fuel tank allows the tractor to operate for longer periods without stopping to refuel. Paired with a fuel-efficient engine, this enables uninterrupted and efficient operations during the busiest seasons.



Dual filter air cleaner for engine longevity

An additional filter protects the tractor's engine from harmful particles, drastically extending the engine life.



Cast iron components for sturdier connections

To perform durably with heavier loads, the rear of the rear of this tractor features sturdy cast-iron components to connect implements. The material enhances efficiency of the hydraulics and helps increase component lifecycles.



Easy to open hood for convenient maintenance

The tractor hood can be opened in one motion, providing easy access to the engine and other systems for daily checks, routine service, and maintenance. The side panel can also be removed easily without the need for specialized tools.

Technical specifications

ENGINE	
Engine manufacturer	TYM T1100N4
Type	Natural aspiration
Gross engine power	24 hp 18 kW
PTO power	17.1 hp 12.8 kW
Rated engine speed	2600 rpm
No. of cylinders	3
Displacement	1175 cc 71.7 cu. in.
Air cleaner	Dual dry
Alternator	12V, 50A
Fuel system	IDI
POWERTRAIN	
Transmission type	HST
No. of speeds	Infinite 2-Range
Max. traveling speed	22.4 km/h 13.9 mph
Brakes	Wet disc
Steering	Hydrostatic
Clutch	N/A
CAPACITIES	
Fuel tank	25 L 6.6 gal
Coolant	5.6 L 5.9 qt
Crankcase	4.3 L 4.5 qt
Transmission/Hydraulics system	17 L 4.5 gal
Front axle	4.5 L 4.8 qt

PTO	
PTO type	Independent
PTO control	Electric/Hydro
PTO rear	540 rpm
HYDRAULIC SYSTEM	
Pump type	Dual gear pump
Implement flow	16.6 L/min 4.4 gpm
Steering flow	10.4 L/min 2.7 gpm
Total flow	26.9 L/min 7.1 gpm
Category, 3-point hitch	I
Hitch lift capacity	696 kg 1534 lb
Hitch lift capacity at 24 inches behind link ends	500 kg 1102 lb
Lift control type	Position
No. of standard remote valves	4-0
DIMENSIONS & WEIGHTS	
Overall length with 3-point hitch	2868 mm 112.9 in.
Overall width	1430 mm 56.3 in.
Wheelbase	1480 mm 58.3 in.
Height to top of ROPS	2514 mm 99.0 in.
Height to top of cabin	-
Min. ground clearance	240 mm 9.4 in.
Min. turn radius with brakes	2502 mm 98.5 in.
Min. turn radius without brakes	2682 mm 105.5 in.
Weight with ROPS	995 kg 2193.6 lb
Weight with cab	-
STANDARD TIRES	
R1 Agricultural - Front	6.0-12 4PR
R1 Agricultural - Rear	9.52-20 6PR
R3 Turf - Front	25x8.5-14 6PR
R3 Turf - Rear	36x13.5-15 4PR
R4 Industrial - Rear	23x8.5-12 4PR
R4 Industrial - Rear	12-16.5 6PR

MM60R-1 Mid-Mount Mower

Attachments

Built with 60-inch working width cutting deck and 5.12-inch transport height, the TYM MM60R-1 mid-mount mower is designed to optimize your cutting time and improve cut quality.

Blade velocity	18362 fpm
Blade length	528.3 mm 20.8 in.
Working width	38.2 mm 1.5 in.

PERFORMANCE	
No. of blades	3 EA
Blade velocity	18362 fpm
Blade length	528.3 mm 20.8 in.
Power rating	14.9-18.6 kW 20-25 hp
GENERAL	
Type	Side discharge
Mounting method	Parallel linkage
Lift linkage type	Lower link lift
Adjustment of increment	Dial gauge
Dial gauge hole	7 EA
Dial gauge gab between hole	12.7 mm 0.5 in.
Dial gauge total gab	76.2 mm 3 in.
Universal joint	Ø21.6 × 525 L
Wheel	4 EA
Assistant wheel	1 EA
Belt	V-Belt
Color	Super RED
Deck thickness	123.4 kg 272 lb



DIMENSIONS & WEIGHTS	
Working width	38.2 mm 1.5 in.
Length	74.3 mm 2.92 in.
Width	7.2 mm 0.28 in.
Height	3.3 mm 0.13 in.
Weight	1524 mm 60 in.
Cutting height	25.4 - 101.6 mm 1 - 4 in.
Transport height	130 mm 5.12 in.

TX2000 Front-End Loader

Attachments

Enhance the functionality of your TYM sub-compact tractor with the TX2000 front-end loader. With impressive lift capacity and height, this TYM front-end loader can help you lift, move and handle material more effectively.

Lift height	2207 mm 86.9 in.
Lift capacity at pivot point (max. height)	626 kgf 1380 lb
Bucket capacity	0.18 cu. m 6.4 cu. ft

CAPACITIES & REACH	
Lift height	2207 mm 86.9 in.
Max. lift height under level bucket	2081 mm 81.9 in.
Clearance with bucket dumped	1641 mm 64.6 in.
Reach at maximum lift height	553 mm 21.8 in.
Max. dump angle	53°
Reach with bucket on ground	1487 mm 58.5 in.
Max. rollback angle	30°
Digging depth	82 mm 3.2 in.
Lift capacity at pivot point (max. height)	626 kgf 1380 lb
Breakout force at ground level, pivot pins	934 kgf 2059 lb
Bucket rollback force at ground line	724 kgf 1596 lb
Bucket capacity	0.18 cu. m 6.4 cu. ft
Self leveling	NA
Relief valve setting (loader control valve)	160 kg/sq. cm 2276 psi
Compatible bucket sizes	66" Front-end loader bucket



DIMENSIONS & WEIGHTS	
Overall height in carry position	1170 mm 46.1 in.
Depth of Attachment (to the back of the inner shell)	423 mm 16.7 in.
Height of Attachment	484 mm 19 in.
Length of Attachment (to pivot pin)	592 mm 23.3 in.
Weight of boom & quick attach mechanism (1)	165 kg 363.8 lb
Weight of mounting frame (2)	53 kg 116.8 lb
Weight of bucket (3)	92 kg 202.8 lb
Loader total weight (1+2+3)	310 kg 683.4 lb
Lift cylinder	45 × 30 mm 1.8 × 1.2 in.
Bucket cylinder	50 × 30 mm 1.97 × 1.2 in.
Attachment used for specification	1520 mm 59.8 in.

CYCLE TIMES	
Boom raising time	4.1 sec
Boom lowering time	2.3 sec
Bucket rollback time	2.6 sec
Bucket dumping time	4.1 sec

COMPATIBLE BUCKET SIZES
TYM's multi-purpose buckets are capable of bulldozing, scraping, loading, metering, moving, and clamping material.
60" Front-End Loader bucket

TB65 Backhoe

Attachments

The TB65 is engineered to handle your scaled-up requirements. This TYM backhoe attachment offers enhanced functionality without compromising balance with an enhanced dig depth and wider swing angle.

Digging depth	2042 mm 80.4 in.
Loading height	1602 mm 63 in.
Backhoe reach	2989 mm 117.7 in.

PERFORMANCE	
Digging depth	2042 mm 80.4 in.
Loading height	1602 mm 63 in.
Max. leveling angle	10°
Angle of departure	15°

CAPACITIES & REACH	
Backhoe reach	2989 mm 117.7 in.
Swing angle	180°
Bucket rotation	180°
Stabilizer spread (lowered position)	1792 mm 70.5 in.
Stabilizer spread (raised position)	1525 mm 60 in.



DIMENSIONS & WEIGHTS	
Transport overhang	1162 mm 45.7 in.
Transport height (max.)	2060 mm 81.1 in.
Compatible bucket sizes	9" backhoe bucket
Compatible bucket sizes	12" backhoe bucket
Compatible bucket sizes	16" backhoe bucket
Compatible bucket sizes	18" backhoe bucket

COMPATIBLE BUCKET SIZES	
TYM's multi-purpose buckets are capable of bulldozing, scraping, loading, metering, moving, and clamping material.	
Small_09	Small_12
Small_16	Small_18

Upgrades for the Series 1, T265

Complement the capabilities of your TYM tractor with compatible accessories and options.

Accessories

- Front counterweights
- Mulching kits



Options

Tire	R3 Turf Tires	F 25x8.5 - 14	R 36x13.5-15
------	---------------	---------------	--------------



Designed for your world

TYM creates tractors that bring together alluring form, advanced function and accessible value. Through Korean expertise in design, engineering and manufacturing, the company helps owners overcome every obstacle as they shape the world around them.

Headquartered in Korea with distribution across North America, Europe, and Asia, and assembly operations in the USA, TYM has been empowering customers for over 70 years.

www.tym.world