F25



Compact, Series 2



A compact tractor that delivers comfort and performance

The F25 is a mid-sized compact tractor that's both robust and efficient. Designed for lasting durability, this Series 2 tractor is ready to take on a range of applications with varying intensities.







1. New iconic hood



3. Ergonomic lever



5. High-capacity fuel tank



2. Comfortable suspension seat



4. 4 wheel drive



6. High visibility instrumental panel



Eco-friendly TYM 4-cylinder Stage-V engine

Equipped with a naturally aspirated engine designed and manufactured by TYM, the tractor is designed to be eco-friendly and fuel-efficient without compromising on performance.



LED work light (optional)

Full front and rear LED work lights facilitate safer operations, particularly in low visibility conditions such as rainy or dusty work environments, or during nighttime tasks.



Tilt steering wheel

The tilt steering wheel allows operators to adjust the position of the steering wheel for a more comfortable driving experience.



Differential lock system and low turning angle

The differential lock system, activated with easily accessible levers, provides enhanced traction in slippery work environments, while a 52° turning angle makes operation in narrow areas much easier.



PTO on/off switch

Safety is a top priority. The PTO switch ensures secure operation of all tractor attachments.



Water-separating fuel filter

The water-separating fuel filter prevents foreign substances from entering the fuel, ensuring better engine starting performance and preventing damage to the machine.

Technical specifications

| ENGINE | |
|--------------------------------|---|
| Engine manufacturer | TYM T1700N6 |
| Туре | Natural aspiration |
| Gross engine power | 24.5 hp 18.3 kW |
| PTO power | 25.9 hp 19.4 kW |
| Rated engine speed | 2100 rpm |
| No. of cylinders | 3 |
| Displacement | 1715 cc 104.7 cu. in. |
| Air cleaner | Dry element |
| Alternator | 12V, 50A |
| Fuel system | Water-cooled diesel |
| POWERTRAIN | |
| Transmission type | Synchro-shuttle |
| No. of speeds | SS: F12 x R12 HST: 3-Range |
| Max. traveling speed | SS: 25.2 km/h 15.7 mph HST: 24.9 km/h 15.5 mph |
| Brakes | Wet, Multi disc |
| Steering | Hydrostatic |
| Clutch | Dry single plate |
| CAPACITIES | |
| Fuel tank | 30 L 7.9 gal |
| Coolant | 5 L 5.3 qt |
| Crankcase | 4.5 L 4.7 qt |
| Transmission/Hydraulics system | 34 L 8.98 gal |
| Front axle | 6.4 L 6.8 qt |

| РТО | |
|---|-----------------------|
| PTO type | Independent |
| PTO control | Electric/Hydro |
| PTO rear | 540/540E rpm |
| HYDRAULIC SYSTEM | |
| Pump type | Gear pump |
| Implement flow | 29.3 L/min 7.7 gpm |
| Steering flow | 15.8 L/min 4.2 gpm |
| Total flow | 45.1 L/min 11.9 gpm |
| Category, 3-point hitch | 1 |
| Hitch lift capacity | 1500 kg 3306 lb |
| Hitch lift capacity at 24 inches behind link ends | 757 kg 1668 lb |
| Lift control type | Position/Draft |
| No. of standard remote valves | 2/2 |
| DIMENSIONS & WEIGHTS | |
| Overall length with 3-point hitch | 3380 mm 133.1 in. |
| Overall width | 1626 mm 64.02 in. |
| Wheelbase | 1670 mm 65.7 in. |
| Height to top of ROPS | 2515 mm 99.02 in. |
| Height to top of cabin | - |
| Min. ground clearance | 443.5 mm 17.46 in. |
| Min. turn radius with brakes | 2550 mm 100.4 in. |
| Min. turn radius without brakes | 2920 mm 115 in. |
| Weight with ROPS | 1431 kg 3154.8 lb |
| Weight with cab | - |

| STANDARD TIRES | |
|-------------------------|--|
| R1 Agricultural - Front | 1: 7-16 6PR 2: 8-16 4PR 3: 280/70R16 4: 215/70R16 |
| R1 Agricultural - Rear | 1: 11.2-24 8PR 2: 12.4-24 6PR 3: 380/85R24 4: 44x18-20 |
| R3 Turf - Front | 1: 215/70R16 2: 260/70R16 3: 27x8.5-15 |
| R3 Turf - Rear | 1: 11.2-24 8PR 2: 420/70R24 3: 41x14-20 |
| R4 Industrial - Front | 1: 10-16.5 2: 240/70R16 3: 240/70R16 4: 240/70R16 5: 200/70R16 |
| R4 Industrial - Rear | 1: 420/70R24 2: 320/70R24 3: 340/85R24 4: 360/70R24 5: 300/80R24 |

Upgrades for the Series 2, F25

Complement the capabilities of your TYM tractor with compatible accessories and options.

Accessories



Options

| Tire | R1 Agricultural Tires | F 8 - 16 4PR | R 12.4-24 8PR |
|------|-----------------------|-------------------|-----------------|
| Tire | R3 Turf Tires | F 27x8.5 - 15 6PR | R 41x14.00 4PR |
| Tire | R4 Industrial Tires | F 10 - 16.5 6PR | R 420/70-24 6PR |



Designed for your world

TYM creates tractors that bring together alluring form, advanced function and accessible value. Through Korean expertise in design, engineering and manufacturing, the company helps owners overcome every obstacle as they shape the world around them.

Headquartered in Korea with distribution across North America, Europe, and Asia, and assembly operations in the USA, TYM has been empowering customers for over 70 years.

www.tym.world