

T4058P

Compact, Series 4
58 hp



A premium compact tractor that delivers power and efficiency

When it comes to all-around productivity, look no further than the T4058P. This compact tractor is designed to boost output, delivering impressive efficiency and deluxe features that have become the hallmark of the TYM Series 4.



1. New iconic hood



3. Electronic 4WD engagement



5. Comfortable suspension seat



2. Digital instrument panel



4. Tilt steering wheel



6. External hitch switch



Eco-friendly TYM Tier 4 engine

Equipped with the Turbo charged company designed-and-made TYM engine, the tractor is designed to be eco-friendly and fuel efficient but makes no compromise on performance and reliability.



MYTYM telematics system

Through MYTYM's remote diagnostics service, check the real-time monitoring, enhanced maintenance and improved operational efficiency.



Power shuttle and D-clutch

Power shuttle enhances efficiency for tasks requiring frequent directional changes in tighter spaces without stepping on the clutch pedal and enhance the maneuverability.



Electronic hydraulic control system

The system allows for easy control of operations for 3pt-hitch control, turn/back up and draft sensitivity adjustment and giving operators full control over their task at hand.



4-Ports front/rear external hydraulic valve

The 4-port rear hydraulic valves support various implements, simplifying tasks such as tilling, plowing, and cargo transport.

Technical specifications

ENGINE	
Engine manufacturer	TYM T2300T1-UTR_4
Type	Turbo charger
Gross engine power	58 hp 43.3 kW
PTO power	48 hp 35 kW
Rated engine speed	2600 rpm
No. of cylinders	4
Displacement	139.5 cu. in. 2286 cc
Air cleaner	Dry element
Alternator	12V, 70A
Fuel system	IDI
POWERTRAIN	
Transmission type	Power shuttle
No. of speeds	F12 x R12
Max. traveling speed	24.04 mph 38.7 km/h
Brakes	Wet, Multi disc
Steering	Hydrostatic
Clutch	Wet Multi disc
CAPACITIES	
Fuel tank	15.32 gal 58 L
Coolant	6.2 qt 5.9 L
Crankcase	4.7 qt 4.5 L
Transmission/Hydraulics system	11.6 gal 44 L
Front axle	6.8 qt 6.4 L

PTO	
PTO type	Independent
PTO control	Wet, Multi-disc
PTO rear	540 rpm
HYDRAULIC SYSTEM	
Pump type	Single gear pump
Implement flow	11.4 gpm 43.2 L/min
Steering flow	5.13 gpm 19.44 L/min
Total flow	16.5 gpm 62.6 L/min
Category, 3-point hitch	II
Hitch lift capacity	4409 lb 2000 kg
Hitch lift capacity at 24 inches behind link ends	3748 lb 1700 kg
Lift control type	Position
No. of standard remote valves	Loader: 4 / Rear: 4
DIMENSIONS & WEIGHTS	
Overall length with 3-point hitch	141.5 in. 3595 mm
Overall width	68.9 in. 1750 mm
Wheelbase	78.7 in. 2000 mm
Height to top of ROPS	104.7 in. 2660 mm
Height to top of cabin	-
Min. ground clearance	18.1 in. 460 mm
Min. turn radius with brakes	(L) 121.9 in. 3098 mm / (R) 125.3 in. 3184 mm
Min. turn radius without brakes	(L) 139.7 in. 3550 mm / (R) 141.9 in. 3606 mm
Weight with ROPS	4506.2 lb 2044 kg
Weight with cab	-
STANDARD TIRES	
R1 Agricultural - Front	9.5-20
R1 Agricultural - Rear	14.9-28
R4 Industrial - Front	10.5/80-18
R4 Industrial - Rear	16.9-24
Golf Tires - Front	29x12.5-15
Golf Tires - Rear	44x18.00-20

Upgrades for the Series 4, T4058P

Complement the capabilities of your TYM tractor with compatible accessories and options.

Accessories



Options

Tire	R1 Agricultural Tires	F 9.5 - 20	R 14.9-28
Tire	R4 Industrial Tires	F 10.5/80 - 18	R 16.9-24



Designed for your world

TYM creates tractors that bring together alluring form, advanced function and accessible value. Through Korean expertise in design, engineering and manufacturing, the company helps owners overcome every obstacle as they shape the world around them.

Headquartered in Korea with distribution across North America, Europe, and Asia, and assembly operations in the USA, TYM has been empowering customers for over 70 years.

www.tym.world