

T6115

Utility, Series 6
111 hp



A powerful utility tractor designed to conquer the most demanding tasks

Engineered to meet the demands of modern agriculture, combining power, efficiency, and advanced technology for unmatched performance. With an enhanced lift capacity, updated hydraulic top link, and integrated telematics, it handles heavy-duty tasks with ease while enabling smarter, data-driven farm management.



1. Hood facelift



3. High-capacity 3-point
hitch



5. Side view mirrors



2. Air-ride full
suspension seat



4. Reverse camera



6. TFT LCD rear monitor
system



Premium cabin

Experience panoramic views, effortless access through dual side doors, and a suite of premium cabin amenities designed to enhance comfort, productivity, and safety.



Smart key with remote start and control

The T6115 Smart Key enables remote engine start, hitch control, and push-button start/stop for added convenience.



Battery shut-off switch

The battery shut-off switch prevents battery discharge and potential malfunction during long-term tractor storage.



Leveling control

Equipped with a proportional control valve and gyro sensor, it detects and corrects vehicle tilt more quickly and precisely. This enables stable operation even on slopes, helping crops grow more evenly and improving productivity.



Smart break

Brake Operation without Clutch (On/Off Switch Type) Improved Driving Convenience



MYTYM telematics

Telematics come standard on the T6115, enabling complete crop management by allowing machines to communicate and share data. Integrating data with artificial intelligence technologies enhances efficiency and productivity and allows you to develop comprehensive farm management technologies.

Technical specifications

ENGINE	
Engine Manufacturer	Deutz
Type	Turbo charge
Gross engine power	111 hp 83 kW
PTO power	109 hp 80 kW
Rated engine speed	2200 rpm
No. of cylinders	4
Displacement	220 cu. in. 3600 cc
Air cleaner	Dual dry
Alternator	12V, 120A
Fuel system	CRDI
POWERTRAIN	
Transmission type	Power shuttle, Power shift
No. of speeds	F32 × R32
Max. traveling speed	23 mph 37 km/h
Brakes	Hydraulic
Steering	Hydrostatic
Clutch	Wet
CAPACITIES	
Fuel tank	31.43 gal 119 L
Coolant	4.8 gal 18.1 L
Crankcase	2.11 gal 8 L
Transmission/Hydraulics system	23.8 gal 90.1 L
Front axle	4.6 gal 17.4 L

PTO	
PTO type	Independent
PTO control	Electro-hydraulic
PTO rear	540/750/1000 rpm
HYDRAULIC SYSTEM	
Pump type	Dual gear pump
Implement flow	14.3 gpm 54.1 L/min
Steering flow	7.1 gpm 27 L/min
Total flow	21.4 gpm 81.1 L/min
Category, 3-point hitch	2
Hitch lift capacity	7294.9 lb 3309 kg
Hitch lift capacity at 24 inches behind link ends	6006.8 lb 2722 kg
Lift control type	Position/Draft
No. of standard remote valves	6
DIMENSIONS & WEIGHTS	
Overall length with 3-point hitch	167.32 in. 4250 mm
Overall width	91.33 in. 2320 mm
Wheelbase	93.7 in. 2380 mm
Height to top of Cabin	112.59 in. 2860 mm
Min. ground clearance	16.7 in. 424.2 mm
Min. turn radius with brakes	(L) 3400 mm 133.9 in. / (R) 3410 mm 134.3 in.
Min. turn radius without brakes	(L) 4050 mm 159.5 in. / (R) 4090 mm 161 in.
Weight with cab	8939 lb 4055 kg
Weight with ROPS	-
STANDARD TIRES	
Agricultural - Front	13.6-24 8PR
Agricultural - Rear	18.4-34 10PR

Upgrades for the Series 6 T6115

Complement the capabilities of your TYM tractor with compatible accessories and options.

ACCESSORIES

Front counterweights





Designed for your world

TYM creates tractors that bring together alluring form, advanced function and accessible value. Through Korean expertise in design, engineering and manufacturing, the company helps owners overcome every obstacle as they shape the world around them.

Headquartered in Korea with distribution across North America, Europe, and Asia, and assembly operations in the USA, TYM has been empowering customers for over 70 years.

www.tym.world