

T130

Utility, Series 6
129 PS



The premium utility tractor redefining excellence through innovation.

Meet TYM's flagship tractor, the T130. This utility tractor seamlessly merges sophisticated design with powerful performance, blending cutting-edge smart technology and premium features to provide the ultimate tractor experience.



1. Backlit logo




3. Push to start button



2. Sideview mirrors with LED




4. Adjustable suspension seat



5. Rear external hydraulic ports (hydraulic top link)



6. Heated rear window



High-powered Deutz engine

Boasting precise German engineering, this engine offers high power and torque even at lower RPMs. Optimized to work with minimal breakdown, this engine offers productive work over a longer lifecycle.



Smart charger and insulated cup holder

The T130 features some of the most premium top-end features for operator convenience, including a wireless smartphone charger and an insulated cupholder that keeps your drink hot or cold, within easy reach from the operator seat.



Telematics

Check the replacement cycle, remote diagnosis, and workload through the mobile app.

1. Remote start and check the status of the tractor.
- Battery, fuel, gear, PTO, oil temperature, and more
2. Review the tractor's work logs
- Hours worked, fuel used, average fuel consumption, and more
3. Receive notifications related to the tractor
- Parts replacement, repairs, emergency alerts, and more



LED work lights for better visibility

Work safely in low-light conditions with brighter lights and a wider field of illumination.



Optional autonomous driving kit

Autonomous driving features available when equipped with an optional ACU:

- Autonomous Driving LV. 1: Straight Assist + Manual Turn and drive straight
- Autonomous Driving LV. 2: Straight assist + automatic turn and drive straight



10.1-inch touchscreen monitor

Use the easy-to-read 10.1-inch touch screen monitor to view vital information such as the vehicle status.



Side and rear work lights

Work lights are located on the sides and rear of the tractor to allow the operator to safely enter and exit the cabin.



Smart key with remote start and control

The T130 smart key enables remote engine starts, hitch control, and push-button start/stop for added convenience.

Technical specifications

| ENGINE | |
|--------------------------------|-------------------------------|
| Engine manufacturer | Deutz TCD3.6L4 |
| Type | Turbo engine |
| Gross engine power | 129 PS 95 kW |
| PTO power | 119 PS 87 kW |
| Rated engine speed | 2200 rpm |
| No. of cylinders | 4 |
| Displacement | 3621 cc 220.96 cu. in. |
| Air cleaner | Dual dry |
| Alternator | 12V, 120A |
| Fuel system | CRDI |
| POWERTRAIN | |
| Transmission type | Power shuttle & 6-speed shift |
| No. of speeds | F36 × R36 |
| Max. traveling speed | 37.4 km/h 23.05 mph |
| Brakes | Wet disc |
| Steering | Hydrostatic |
| Clutch | Wet/Multi disc |
| CAPACITIES | |
| Fuel tank | 190 L 50.19 gal |
| Coolant | 18 L 19 qt |
| Crankcase | 8 L 8.5 qt |
| Transmission/Hydraulics system | 100 L 26.4 gal |
| Front axle | 18.1 L 4.8 gal |

| PTO | |
|---|---|
| PTO type | Independent |
| PTO control | Electric/Hydro |
| PTO rear | 540/750/1000 rpm |
| HYDRAULIC SYSTEM | |
| Pump type | Dual gear pump |
| Implement flow | 76.19 L/min 20.1 gpm |
| Steering flow | 34.41 L/min 9.1 gpm |
| Total flow | 110.6 L/min 29.2 gpm |
| Category, 3-point hitch | Cat 2 |
| Hitch lift capacity | 3747 kg 8260.7 lb |
| Hitch lift capacity at 24 inches behind link ends | 3635 kg 8014.3 lb |
| Lift control type | Position/Draft/TBS |
| No. of standard remote valves | 6 |
| DIMENSIONS & WEIGHTS | |
| Overall length with 3-point hitch | 4490 mm 176.77 in. |
| Overall width | 2360 mm 92.91 in. |
| Wheelbase | 2590 mm 101.96 in. |
| Height to top of cabin | 2940 mm 115.74 in. |
| Height to top of ROPS | - |
| Min. ground clearance | 410 mm 16.14 in. |
| Min. turn radius with brakes | (L) 4210 mm 165.75 in. / (R) 4230 mm 165.53 in. |
| Min. turn radius without brakes | (L) 4740 mm 186.61 in. / (R) 4800 mm 188.98 in. |
| Weight with cab | 4545 kg 10020 lb |
| Weight with ROPS | - |
| Track width | F: 1880 mm / R: 1815 mm |
| STANDARD TIRES | |
| Agricultural - Front | 380/85 R 24 |
| Agricultural - Rear | 460/85 R 38 |

LX125P Front-End Loader

Attachments

Engineered to lift higher and lift heavier materials, the TYM LX125P is optimized for superior material handling. Taking advantage of the power and performance of the TYM utility tractors, the LX125P is compatible with the T130.

| | |
|--|--------------------|
| Lift height | 4114 mm 162 in. |
| Lift capacity at pivot point (max. height) | 2456 kgf 5415 lb |
| Self leveling | Available |

| CAPACITIES & REACH | |
|---|-----------------------------|
| Lift height | 4114 mm 162 in. |
| Max. lift height under level bucket | 3873 mm 152.5 in. |
| Clearance with bucket dumped | 3227 mm 127 in. |
| Reach at maximum lift height | 379 mm 14.9 in. |
| Max. dump angle | 60° |
| Reach with bucket on ground | 2513 mm 98.9 in. |
| Max. rollback angle | 52° |
| Digging depth | 155 mm 6.1 in. |
| Lift capacity at pivot point (max. height) | 2456 kgf 5415 lb |
| Breakout force at ground level, pivot pins | 3002 kgf 6618 lb |
| Bucket rollback force at ground line | 3118 kgf 6874 lb |
| Self leveling | Available |
| Relief valve setting (loader control valve) | 210 kg/sq. cm 2987 psi |
| Compatible bucket sizes | 66" Front-end loader bucket |



| DIMENSIONS & WEIGHTS | |
|--|----------------------------|
| Overall height in carry position | 2194 mm 86.4 in. |
| Depth of Attachment (to the back of the inner shell) | 579 mm 22.8 in. |
| Height of Attachment | 563 mm 22.2 in. |
| Length of Attachment (to pivot pin) | 886 mm 34.9 in. |
| Weight of boom & quick attach mechanism (1) | 549 kg 1210 lb |
| Weight of mounting frame (2) | 268 kg 591 lb |
| Weight of bucket (3) | 203 kg 448 lb |
| Loader total weight (1+2+3) | 1020 kg 2249 lb |
| Lift cylinder | 80 × 45 mm 3.1 × 1.8 in. |
| Bucket cylinder | 75 × 40 mm 3.0 × 1.6 in. |
| Attachment used for specification | 2330 mm 92 in. |
| CYCLE TIMES | |
| Boom raising time | 4.4 sec |
| Boom lowering time | 2.8 sec |
| Bucket rollback time | 2.6 sec |
| Bucket dumping time | 3.6 sec |

Upgrades for the Series 6, T130

Complement the capabilities of your TYM tractor with compatible accessories and options.

Accessories

Front counterweights





Designed for your world

TYM creates tractors that bring together alluring form, advanced function and accessible value. Through Korean expertise in design, engineering and manufacturing, the company helps owners overcome every obstacle as they shape the world around them.

Headquartered in Korea with distribution across North America, Europe, and Asia, and assembly operations in the USA, TYM has been empowering customers for over 70 years.

www.tym.world