

# T3040

Compact, Series 3  
37 PS



# A compact tractor that doesn't compromise on performance

With its compact body, power steering, and a range of practical work features, it supports more convenient and efficient operation even in narrow orchards and small farms.



1. Digital Instrument Panel



3. Seat



2. Forward/Reverse lever



4. Fuel tank



5. Rear external hydraulic valve, 4 ports



6. Battery disconnect switch



### High-output, eco-friendly Yanmar engine

Built with the proven durability and stable performance of a Yanmar engine, it delivers dependable power that helps improve overall work quality.

Complies with emissions regulations  
Excellent fuel efficiency and low noise help reduce operator fatigue  
Proven durability and reliability for stable operation



### Strong traction, longer working hours

Superior pulling performance in its class and a large-capacity fuel tank help improve both productivity and operating endurance.



### Operator-focused controls and convenient operability

An ergonomically designed seat and intuitively arranged controls enhance operator comfort and ease of use.



### Auto PTO & PTO on/off switch

With Auto PTO enabled, PTO stops when the implement is raised, and PTO power can be quickly engaged or disengaged with a single switch.



### 3-speed PTO

With a 3-speed PTO, operators can efficiently perform a wide range of tasks by matching PTO output to the working conditions.



### Rear LED work light

Provides clear visibility for stable, reliable nighttime operations.

# Technical specifications

## ENGINE

Engine Manufacturer	Yanmar 3TNV88C
Type	Natural aspiration
Gross engine power	37 PS   28 kW
PTO power	30 PS   22 kW
Rated engine speed	3000 rpm
No. of cylinders	3
Displacement	1642 cc   100.200 cu. in.
Air cleaner	Dry element
Alternator	12V, 70A
Fuel system	CRDi

## POWERTRAIN

Transmission type	Mechanical
No. of speeds	F12 × R12
Max. traveling speed	25.3 km/h   15.72 mph
Brakes	Wet disc
Steering	Hydrostatic
Clutch	Dry disc

## CAPACITIES

Fuel tank	33 L   8.7 gal
Coolant	4.8 L   5.1 qt
Crankcase	3.2 L   3.3 qt
Transmission/Hydraulics system	36 L   9.5 gal
Front axle	8.2 L   8.7 qt

## PTO

PTO type	Independent
PTO control	Electric/Hydro
PTO rear	540/750/1000 rpm

## HYDRAULIC SYSTEM

Pump type	Single gear pump
Implement flow	21.6 L/min   5.7 gpm
Steering flow	15.6 L/min   4.1 gpm
Total flow	37.2 L/min   9.8 gpm
Category, 3-point hitch	Cat 1
Hitch lift capacity	880 kg   1940 lb
Hitch lift capacity at 24 inches behind link ends	538 kg   1186 lb
Lift control type	Position
No. of standard remote valves	4

## DIMENSIONS & WEIGHTS

Overall length with 3-point hitch	3086 mm   121.5 in.
Overall width	1460 mm   57.5 in.
Wheelbase	1640 mm   64.6 in.
Height to top of ROPS	2600 mm   102.8 in.
Height to top of Cabin	-
Min. ground clearance	431 mm   17 in.
Min. turn radius with brakes	2610 mm   102.8 in.
Min. turn radius without brakes	2870 mm   113 in.
Weight with ROPS	1390 kg   3064 lb
Weight with cab	-
Track width	F: 1190 mm / R: 1050 mm

## STANDARD TIRES

Agricultural - Front	8-16
Agricultural - Rear	12.4-24



# Designed for your world

TYM creates tractors that bring together alluring form, advanced function and accessible value. Through Korean expertise in design, engineering and manufacturing, the company helps owners overcome every obstacle as they shape the world around them.

Headquartered in Korea with distribution across North America, Europe, and Asia, and assembly operations in the USA, TYM has been empowering customers for over 70 years.

[www.tym.world](http://www.tym.world)